

# NOBA 50 suspended canopy ceiling

049-53139137W 005-2601297



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 67°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 715      | 1.31  |
| 2     | 179      | 2.63  |
| 3     | 79       | 3.94  |
| 4     | 45       | 5.26  |
| 5     | 29       | 6.57  |



## General

brushed brass \_\_\_\_\_

Cable traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

752 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 97 | R<sub>f</sub>: 91 | R<sub>t(1-15)</sub>: 87 \_\_\_\_\_

MR 0.52 | MDER 0.47 \_\_\_\_\_

## Optical

wide flood | beam angle 67° \_\_\_\_\_

## Electrical

Casambi \_\_\_\_\_

PC3 | 220-240 V \_\_\_\_\_

system 6.5 W | fixture 4.8 W \_\_\_\_\_

system 116 lm/W<sup>1</sup> | fixture 155 lm/W<sup>2</sup> \_\_\_\_\_

150 mA \_\_\_\_\_

## Physical

diameter 50 mm | height 50 mm \_\_\_\_\_

cable length 2500 mm \_\_\_\_\_

<sup>1</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses



# NOBA 50 suspended canopy ceiling

049-53139137W 005-2601297



Project / Type

Notes

Count / Date

### Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF               | 0.964  | 0.923  | 0.884  | 0.847  | 0.811  |
| LSF                | 1      | 1      | 1      | 1      | 1      |

MF

LMF × RSMF × LLMF × LSF

MF

Maintenance Factor

LMF<sup>a</sup>

Luminaire Maintenance Factor

RSMF<sup>a</sup>

Room Surface Maintenance Factor

LLMF

Lamp Lumens Maintenance Factor

LSF

Lamp Survival Factor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

### Mounting accessories

#### HOOK surface

| COLOUR        | Ø (MM) | ARTICLE NUMBER(S) |
|---------------|--------|-------------------|
| traffic white | 16     | 030-1000017       |
| jet black     | 16     | 030-1000018       |



### Optional electrical accessories

#### DIN RAIL POWER SUPPLY

| L·W·H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 72-90-63   | 005-6520210       |



#### DIN RAIL LED DRIVER

| TYPE                    | L·W·H (MM) | ARTICLE NUMBER(S) |
|-------------------------|------------|-------------------|
| 200 - 1050 mA   2 x 42W | 36-88-59   | 005-6121030       |

