

NOBA 50 suspended canopy ceiling

049-53130137W 005-2601298



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

Light distribution



wide flood 67°

h (m)	E0° (lx)	ø (m)
1	743	1.31
2	186	2.63
3	83	3.94
4	46	5.26
5	30	6.57



General

brushed brass

Cable traffic white

IP20

782 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 | R_f: 90 | R_{f[-15]}: 87

MR 0.6 | MDER 0.54

Optical

wide flood | beam angle 67°

Electrical

Casambi

PC3 | 220-240 V

system 6.5 W | fixture 4.8 W

system 120 lm/W ¹ | fixture 162 lm/W ²

150 mA

Physical

diameter 50 mm | height 50 mm

cable length 2500 mm

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency

² incl. consideration of optical losses & internal control unit losses

