

# NOBA 50 suspended canopy ceiling

049-53131177W 005-2601298



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 67°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 779      | 1.31  |
| 2     | 195      | 2.63  |
| 3     | 87       | 3.94  |
| 4     | 49       | 5.26  |
| 5     | 31       | 6.57  |



## General

traffic white | RAL 9016 <sup>1</sup> \_\_\_\_\_

Cable traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

819 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 98 | R<sub>f</sub>: 90 | R<sub>[-15]</sub>: 88 \_\_\_\_\_

MR 0.8 | MDER 0.72 \_\_\_\_\_

## Optical

wide flood | beam angle 67° \_\_\_\_\_

## Electrical

Casambi \_\_\_\_\_

PC3 | 220-240 V \_\_\_\_\_

system 6.5 W | fixture 4.8 W \_\_\_\_\_

system 126 lm/W <sup>2</sup> | fixture 169 lm/W <sup>3</sup> \_\_\_\_\_

150 mA \_\_\_\_\_

## Physical

diameter 50 mm | height 50 mm \_\_\_\_\_

cable length 2500 mm \_\_\_\_\_

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>3</sup> incl. consideration of optical losses & internal control unit losses

