

# NOBA 40 suspended trim

049-53101167W 005-3521118 002-90811



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 69°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 698      | 1.37  |
| 2     | 175      | 2.74  |
| 3     | 78       | 4.12  |
| 4     | 44       | 5.49  |
| 5     | 28       | 6.86  |



### General

brushed aluminium  
Cable traffic white  
IP20  
790 lm

### LED

4000 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 98 | R<sub>f</sub>: 90 | R<sub>f[1-15]</sub>: 88  
MR 0.8 | MDER 0.72

### Optical

wide flood | beam angle 69°  
PstLM ≤ 1.0 <sup>1</sup> | SVM ≤ 0.4 <sup>1</sup>

### Electrical

PC3 | 220-240 V  
system 6.5 W | fixture 4.9 W  
system 122 lm/W <sup>2</sup> | fixture 162 lm/W <sup>3</sup>  
150 mA

### Physical

diameter 40 mm | height 40 mm  
cable length 2500 mm

### Cutout

diameter 65 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>3</sup> incl. consideration of optical losses & internal control unit losses

