

# NOBA 40 suspended canopy ceiling

049-53100167W 005-2601297



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

## Light distribution



wide flood 69°

h (m)	E0° (lx)	ø (m)
1	667	1.37
2	167	2.74
3	74	4.12
4	42	5.49
5	27	6.86



### General

brushed aluminium

Cable traffic white

IP20

755 lm

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 90 | R<sub>[-15]</sub>: 87

MR 0.6 | MDER 0.54

### Optical

wide flood | beam angle 69°

### Electrical

Casambi

PC3 | 220-240 V

system 6.5 W | fixture 4.9 W

system 116 lm/W <sup>1</sup> | fixture 155 lm/W <sup>2</sup>

150 mA

### Physical

diameter 40 mm | height 40 mm

cable length 2500 mm

<sup>1</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses

