

# ENVIVA spotline direct / indirect

suspended  
067-12140117W



Project / Type

Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

## Product drawing



### General

aluminium raw

Inset traffic white

Cable black

IP20

indirect 2800 lm

### LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>f(1-15)</sub>: 89

MR 0.61 | MDER 0.55

### Optical

spotline

PstLM ≤ 1.0<sup>1 2</sup> | SVM ≤ 0.4<sup>1 2</sup>

### Electrical

DALI-2 | 1 DALI Addr.

PC2 | 42 V

system 44 W | fixture 38 W

56 mA

### Physical

length 1204 mm | width 45 mm | height 15.4 mm

<sup>1</sup> 900mA <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions

