

# ENVIVA spotline direct / indirect

suspended  
067-12155B77W



Project / Type

Notes

Count / Date



General
traffic white   RAL 9016 <sup>1</sup>
Inset traffic white
Cable white
IP20
indirect 3250 lm   direct 3340 lm
total 6590 lm
fixture 174 lm/W <sup>2</sup>

LED
3000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.56   MDER 0.51


Optical
spotline
UGR ≤ 13   ≥65° <1500 cd/m²
PstLM ≤ 1.0³ ⁴   SVM ≤ 0.4³ ⁴

Electrical
DALI-2 essential sensor   1 DALI Addr.
brightness & presence
PC2   42 V
system 43 W   fixture 38 W
50 mA


Physical
length 1545 mm   width 45 mm   height 15.4 mm

Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> 900mA <sup>4</sup> Value of containing product at full load (undimmed)

## Installation instructions

