

# ENVIVA louver direct / indirect

suspended  
067-02155B04X



Project / Type

Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

### Light distribution



### Product drawing



### General

aluminium raw
Inset chrome
Cable white
IP20
indirect 3100 lm   direct 3230 lm
total 6330 lm
fixture 177 lm/W <sup>1</sup>

### LED

3000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.56   MDER 0.51

### Optical

super wide flood
UGR ≤ 13   ≥65° <1500 cd/m²
PstLM ≤ 1.0² <sup>3</sup>   SVM ≤ 0.4² <sup>3</sup>

### Electrical

DALI-2 essential sensor   1 DALI Addr.
brightness & presence
PC2   42 V
system 41 W   fixture 36 W
47 mA

### Physical

length 1545 mm   width 45 mm   height 15.4 mm
---

<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> 850mA <sup>3</sup> Value of containing product at full load (undimmed)

### Installation instructions



# ENVIVA louver direct / indirect

suspended  
067-02155B04X



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1

MF

MF

LMF<sup>a</sup>

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF<sup>a</sup>

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Mounting accessories

### CANOPY

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
traffic white	112-112-35	005-2611037
jet black	112-112-35	005-2611038
traffic white	112-112-35	005-2611137
jet black	112-112-35	005-2611138

