

# ENVIVA louver direct / indirect

suspended


067-02155178X



Project / Type


Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

## Light distribution



## Product drawing



## General

traffic white | RAL 9016 <sup>1</sup>

Inset black

Cable white

IP20

indirect 3100 lm | direct 3230 lm

total 6330 lm

fixture 177 lm/W <sup>2</sup>

## LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

## Optical

super wide flood

UGR ≤ 13 | ≥65° <1500 cd/m<sup>2</sup>

PstLM ≤ 1.0<sup>3</sup> <sup>4</sup> | SVM ≤ 0.4<sup>3</sup> <sup>4</sup>

## Electrical

DALI-2 | 1 DALI Addr.

PC2 | 42 V

system 41 W | fixture 36 W

47 mA

## Physical

length 1504 mm | width 45 mm | height 15.4 mm

<sup>1</sup> RAL code

<sup>2</sup> incl. consideration of optical losses & internal control unit losses

<sup>3</sup> 850 mA <sup>4</sup> Value of containing product at full load (undimmed)

## Installation instructions

