

ENVIVA louver direct / indirect

suspended

067-02151B74X



Project / Type

Notes

Count / Date



General

traffic white | RAL 9016 ¹

Inset chrome

Cable white

IP20

indirect 2880 lm | direct 3010 lm

total 5890 lm

fixture 165 lm/W ²

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_r: 92 | R_{t(1-15)}: 90

MR 0.81 | MDER 0.74

Optical

super wide flood

UGR ≤ 13 | ≥65° <1500 cd/m²

PstLM ≤ 1.0^{3 4} | SVM ≤ 0.4^{3 4}

Electrical

DALI-2 essential sensor | 1 DALI Addr.

brightness & presence

PC2 | 42 V

system 41 W | fixture 36 W


47 mA

Physical


length 1545 mm | width 45 mm | height 15.4 mm

Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

Light distribution



Product drawing



¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ 850mA ⁴ Value of containing product at full load (undimmed)

Installation instructions

