

ENVIVA spotline direct / indirect

suspended

067-12155108W



Project / Type


Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

Light distribution



Product drawing



General

aluminium raw

Inset jet black

Cable white

IP20

indirect 3250 lm | direct 3160 lm

total 6410 lm

fixture 170 lm/W ¹

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

spotline

UGR ≤ 10 | ≥ 65° < 1500 cd/m²

PstLM ≤ 1.0^{2 3} | SVM ≤ 0.4^{2 3}

Electrical

DALI-2 | 1 DALI Addr.

PC2 | 42 V

system 43 W | fixture 38 W

50 mA

Physical

length 1504 mm | width 45 mm | height 15.4 mm

¹ incl. consideration of optical losses & internal control unit losses
² 900mA ³ Value of containing product at full load (undimmed)

Installation instructions

