

# ENVIVA spotlight direct / indirect

suspended  
067-12151119W



Project / Type


Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

## Light distribution



## Product drawing



## General

aluminium raw  
Inset gold  
Cable black  
IP20  
indirect 3030 lm | direct 3090 lm  
total 6120 lm  
fixture 162 lm/W <sup>1</sup>

## LED

4000 K  
CRI ≥ 90  
L90 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 99 | R<sub>r</sub>: 92 | R<sub>t(1-15)</sub>: 90  
MR 0.81 | MDER 0.74

## Optical

spotline  
UGR ≤ 10 | ≥ 65° < 1500 cd/m<sup>2</sup>  
PstLM ≤ 1.0<sup>2 3</sup> | SVM ≤ 0.4<sup>2 3</sup>

## Electrical

DALI-2 | 1 DALI Addr.  
PC2 | 42 V  
system 43 W | fixture 38 W  
50 mA

## Physical

length 1504 mm | width 45 mm | height 15.4 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> 900 mA <sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions

