

ENVIVA spotline direct / indirect

suspended
067-12150B77W



Project / Type

Notes

Count / Date



General
traffic white RAL 9016 ¹
Inset traffic white
Cable white
IP20
indirect 2800 lm direct 2880 lm
total 5680 lm
fixture 150 lm/W ²


LED
3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 R _r : 91 R _{t(1-15)} : 89
MR 0.61 MDER 0.55

Optical
spotline
UGR ≤ 10 ≥65° <1500 cd/m ²
PstLM ≤ 1.0 ^{3 4} SVM ≤ 0.4 ^{3 4}


Electrical
DALI-2 essential sensor 1 DALI Addr.
brightness & presence
PC2 42 V
system 43 W fixture 38 W
50 mA

Physical
length 1545 mm width 45 mm height 15.4 mm

Light distribution



Product drawing



¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ 900mA ⁴ Value of containing product at full load (undimmed)

Installation instructions



ENVIVA spotline direct / indirect

suspended
067-12150B77W



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	37
B16	60
C10	37
C16	60

Mounting accessories

CANOPY

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
traffic white	112-112-35	005-2611037
jet black	112-112-35	005-2611038
traffic white	112-112-35	005-2611137
jet black	112-112-35	005-2611138

