

# ENVIVA louver direct / indirect

suspended  
067-02145B14X



Project / Type

Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

### Light distribution



### Product drawing



### General

aluminium raw  
Inset chrome  
Cable black  
IP20  
indirect 3080 lm | direct 3180 lm  
total 6260 lm  
fixture 175 lm/W <sup>1</sup>

### LED

3000 K  
CRI ≥ 80  
L90 / 50000 h  
initial MacAdam ≤ 3 SDCM  
MR 0.56 | MDER 0.51

### Optical

super wide flood  
UGR ≤ 16 | ≥65° <1500 cd/m<sup>2</sup>  
PstLM ≤ 1.0<sup>2</sup> <sup>3</sup> | SVM ≤ 0.4<sup>2</sup> <sup>3</sup>

### Electrical

DALI-2 essential sensor | 1 DALI Addr.  
brightness & presence  
PC2 | 42 V  
system 41 W | fixture 36 W  
53 mA

### Physical

length 1245 mm | width 45 mm | height 15.4 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> 850mA <sup>3</sup> Value of containing product at full load (undimmed)

### Installation instructions

