

ENVIVA spotline direct / indirect

suspended


067-12145B18W



Project / Type


Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

Product drawing



General

aluminium raw

Inset jet black

Cable black

IP20

indirect 3250 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

spotline

PstLM ≤ 1.0¹ 2 | SVM ≤ 0.4¹ 2

Electrical

DALI-2 essential sensor | 1 DALI Addr.

brightness & presence

PC2 | 42 V

system 44 W | fixture 38 W

56 mA

Physical

length 1245 mm | width 45 mm | height 15.4 mm

¹ 900mA ² Value of containing product at full load (undimmed)

Installation instructions

