

ENVIVA louver direct / indirect

suspended
067-02140104X



Project / Type

Notes

Count / Date



Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 45 x 15 mm); no visible screws; surface raw or powder coated; pendant fitting with cable suspension; can be adjusted to any height; incl. feeder cable; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with symmetrical light distribution; direct / indirect light distribution; canopy for through wiring (separately available); converter included in canopy; optionally with sensor

Light distribution



Product drawing



General

aluminium raw
Inset chrome
Cable white
IP20
indirect 2650 lm | direct 2740 lm
total 5390 lm
fixture 151 lm/W ¹

LED

3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 99 | R_r: 91 | R_{t(1-15)}: 89
MR 0.61 | MDER 0.55

Optical

super wide flood
UGR ≤ 16 | ≥ 65° < 1500 cd/m²
PstLM ≤ 1.0 ^{2 3} | SVM ≤ 0.4 ^{2 3}

Electrical

DALI-2 | 1 DALI Addr.
PC2 | 42 V
system 41 W | fixture 36 W
53 mA

Physical

length 1204 mm | width 45 mm | height 15.4 mm

¹ incl. consideration of optical losses & internal control unit losses
² 850 mA ³ Value of containing product at full load (undimmed)

Installation instructions

