

FINA SUPPORT lead 30°

011-139AQ216A



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); specially computed foil for asymmetrical light distribution; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase Standing
white aluminium RAL 9006 ¹
IP20
Interior
869 lm
1500 lm/m
optical inset 92 lm/W ²

LED

3500 K
CRI ≥ 97
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 100 R _f : 97 R _{f(1-5)} : 96
MR 0.71 MDER 0.64

Optical

asymmetric

Electrical

excl. driver
PC3 24 V
fixture 12.4 W
optical inset 9.4 W
22 W/m
24 V

Physical

length 621 mm width 9 mm height 9 mm
--

¹ RAL code ² incl. consideration of optical losses

Installation instructions

