

FINA SUPPORT opal 30°

011-139BB116O



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase Standing
white aluminium RAL 9006 ¹
IP20
Interior
1250 lm
1310 lm/m
optical inset 81 lm/W ²

LED

4000 K
CRI ≥ 97
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 100 R _f : 96 R ₍₁₋₁₅₎ : 98
MR 0.86 MDER 0.78

Optical

Opal opal (lambertsch)

Electrical

excl. driver
PC3 24 V
fixture 20.4 W
optical inset 15.5 W
21 W/m
24 V

Physical

length 1006 mm width 9 mm height 9 mm

¹ RAL code ² incl. consideration of optical losses

Installation instructions

