

FINA SUPPORT opal

011-129AX216O



Project / Type


Notes

Count / Date



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in white aluminium; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Standing

white aluminium | RAL 9006 ¹

IP20

Interior

1070 lm

1310 lm/m

optical inset 80 lm/W ²

LED

3500 K

CRI ≥ 97

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 | R_f: 97 | R_(f-15): 96

MR 0.71 | MDER 0.64

Optical

Opal | opal (lambertsch)

Electrical

excl. driver

PC3 | 24 V

fixture 17.6 W

optical inset 13.3 W

22 W/m

24 V

Physical

length 866 mm | width 9 mm | height 9 mm

¹ RAL code ² incl. consideration of optical losses

Installation instructions

