



Project / Type


Notes

Count / Date



Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Recessed

white aluminium | RAL 9006 ¹

IP20

Interior

677 lm

1170 lm/m

optical inset 72 lm/W ²

LED

3000 K

CRI ≥ 97

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_r: 96 | R_{t[1-15]}: 97

MR 0.68 | MDER 0.61

Optical

Opal | opal (lambertsch)

Electrical

excl. driver

PC3 | 24 V

fixture 12.4 W

optical inset 9.4 W

21 W/m

24 V

Physical

length 621 mm | width 9 mm | height 9 mm

0.03 kg

¹ RAL code ² incl. consideration of optical losses