

# FINA SUPPORT opal

011-12011180



Project / Type

Notes

Count / Date



General

Showcase | Standing

rotation 360°

black | RAL 9021 <sup>1</sup>

IP20

Interior

84 lm

1240 lm/m

optical inset 76 lm/W <sup>2</sup>

LED

4000 K

CRI ≥ 97

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 96 | R<sub>f[1-15]</sub>: 97

MR 0.68 | MDER 0.61

Optical

Opal | opal (lambertsch)

Electrical

excl. driver

PC3 | 24 V

fixture 1.5 W

optical inset 1.1 W

21 W/m

24 V

Physical

length 100 mm | width 9 mm | height 9 mm


<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

Installation instructions



Miniature rectangular lamp made of aluminium; angular design; surface lacquered in black; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

