



Project / Type

Notes

Count / Date



General

Showcase | Recessed

black | RAL 9021¹

IP20

Interior

1440 lm

1280 lm/m

optical inset 79 lm/W²

LED

3500 K

CRI ≥ 97

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 | R_f: 97 | R_{f(1-5)}: 96

MR 0.71 | MDER 0.64

Optical

Opal | opal (lambertsch)

Electrical

excl. driver

PC3 | 24 V

fixture 24.0 W

optical inset 18.2 W

21 W/m


24 V

Physical

length 1181 mm | width 9 mm | height 9 mm

Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); completely homogeneously illuminated, satinised PMMA cover; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² incl. consideration of optical losses