



Project / Type

Notes

Count / Date



Miniature linear light inset made of aluminium; tubular design; surface lacquered in black; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with $32^\circ \times 46^\circ$ beam; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Showcase | Recessed

black | RAL 9021¹

IP20

Interior

88 lm

optical inset 80 lm/W²

LED

3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 102 | R_f: 94 | R_{f(1-15)}: 95

MR 0.61 | MDER 0.55

Optical

medium | beam angle $32^\circ \times 46^\circ$

Electrical

excl. driver

PC3 | 24 V

fixture 1.4 W

optical inset 1.1 W

24 V

Physical

length 66 mm | width 9 mm | height 9 mm

0.01 kg

¹ RAL code ² incl. consideration of optical losses