

FLOW 320

surface


073-013153XO



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Surface _____

special colours _____

IP40 _____

2000 lm _____

LED

3000 K _____

CRI \geq 80 _____

L90 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam \leq 3 SDCM _____

MR 0.44 _____

MDER 0.49 _____

Optical

Opal _____

Electrical

DALI-2 _____

15.4 W _____

PC1 220-240V _____

130 lm/W _____

1 DALI Addr. _____

Physical

length 311 mm _____


width 311 mm _____

height 46 mm _____


2.1 kg _____

Square light fitting made of aluminium; flat design (luminaire housing 35mm); surface special colours powder coated; suitable for wall or ceiling mounting; luminaire housing set 11mm away from wall or ceiling; convenient quick mounting system without tools; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; completely homogeneously illuminated, satin PMMA cover; same luminance for all size versions; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



FLOW 320

surface

073-013153XO



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	21
B13	28
B16	35
B20	44
C10	35
C13	46
C16	58
C20	73

Other accessories

DISMOUNTING TOOL

ARTICLE NUMBER(S)
073-0100000

