## **SETA** linear direct

ceiling / suspended system 074-5006637B



Project / Type


Notes

Count / Date



Luminaire housing made of extruded aluminium profile; extremely slim design (only  $\emptyset$  61 mm) linear; converter integrated into luminaire housing; no visible screws; for lighting systems; surface white powder coated; for ceiling surface mounting or suspended mounting (1500 mm cable suspension as an accessory); with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; extruded profile for improved thermal management; light colour 4000 K; binning initial MacAdam  $\le$  3 SDCM; CRI  $\ge$  80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high gloss reflector with faceted design; Reflector black; UGR  $\le$  19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65°  $\le$  1500 cd/m², degree of protection IP20; PC1 220-240V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## **Light distribution**



## **Product drawing**









#### General

Ceiling, Suspended	
white, RAL9010 1	
Reflector black	
IP20	
3620 lm	

#### **LED**

#### Optical

Reflector	
Symmetric	
UGR < 19 . ≥65° <1500 cd/m²	

#### **Electrical**

DALI-2	
22.6 W	
PC1 220-240V	
160 lm/W	
1 DALI Addr.	

#### **Physical**

length 1700 mm	
width 60 mm	
height 60 mm	

<sup>1</sup> RAL code

# Installation instructions



# Lighting calculator



09.06.2023

## **SETA** linear direct

ceiling / suspended system 074-5006637B



Notes	
-------	--

## **Circuit Breaker Types**

Automatic Circuit Breaker Type	Number of Fixtures
B10	31
B13	40
B16	50
B20	62
C10	52
C13	67
C16	85
C20	104

### **MOUNTING**

#### **END CAPS**

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
white	60	074-5090017
black	60	074-5090018



## **MOUNTING**

## LINEAR CONNECTOR

**ARTICLE NUMBER(S)** 074-5091110 074-6091120



## CORNER CONNECTOR

TYPE	COLOUR	L·W·H (MM)	ARTICLE NUMBER(S)
90°   incl. through wire 5 × 1.5 mm <sup>2</sup>	white	60.250.250	074-5091217
90°   incl. through wire 5 × 1.5 mm <sup>2</sup>	black	60.250.250	074-5091218

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com





## **SETA** linear direct

ceiling / suspended system 074-5006637B



Notes			

## **MOUNTING**

#### CEILING FASTENER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	10	050-2041217
jet black	10	050-2041218

## **CABLE SUSPENSION**

COLOUR	ARTICLE NUMBER(S)
chrome	005-2152110

### **CANOPY / FEEDER CABLE**

TYPE	COLOUR	ARTICLE NUMBER(S)	
5 x 1,5 mm <sup>2</sup>	pure white	005-2212417	
5 x 1,5 mm <sup>2</sup>	jet black	005-2212418	- "

## THROUGH WIRE

TYPE	ARTICLE NUMBER(S)
5 x 1,5 mm <sup>2</sup>   10 pieces	004-90005

### **OPTICAL**

### **BLIND COVER**

TYPE 250 mm	COLOUR white	<b>ARTICLE NUMBER(S)</b> 074-5099107
250 mm	black	074-5099108
500 mm	white	074-5099117
500 mm	black	074-5099118

