
Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
up to 136 lm/W
L85 / 50000 h
DALI-2, non DIM
Opal
IP50

Types



Colours

Light distributions

SONO FLEX

recessed

EN Round recessed luminaire in aluminium, consisting of (SONO) light housing and recessed housing; housing with trim suitable for installation in plasterboard ceilings; suitable for ceiling thickness of 10-25 mm; optionally: installation in concrete ceilings with a special installation housing (available as an accessory); surface powder coated; luminaire installs in housing without tools optionally flush or protruding by 25 mm; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; energy-efficient LEDs with very good colour rendering; luminaire with 2 cable openings and plug-in terminals for through wiring

DE Runde Einbauleuchte aus Aluminium, bestehend aus Leuchtenkörper (SONO) und Einbaugehäuse; Gehäuse mit umlaufendem Rand geeignet für den Einbau in Gipskartondecken; geeignet für Deckenstärken von 10-25 mm; optional: Einbau in Betondecken mittels Betoneinbaugehäuse (als Zubehör erhältlich); Oberfläche pulverbeschichtet; Leuchte wahlweise deckenbündig oder 25 mm hervorstehend werkzeuglos im Gehäuse einsetzbar; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; gleiche Leuchtdichte bei allen Größenvarianten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Leuchte mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung



DiiA® standards 251, 252, 253




flexible jut out 0 or 25 mm




dust & insect protection (IP 50)



tunable white 2700 – 6500 K (optional)








SONO FLEX 350 trim


CRI ≥ 80 · 220-240 V · DALI 1 ADDR. · IP50 · X-PERT

OPAL pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.9 W	3000 K	1940 lm	122 lm/W	0 6 3 - 3 2 3 8 5 ◆ 7 O
	4000 K	2050 lm	129 lm/W	0 6 3 - 3 2 3 8 6 ◆ 7 O








SONO FLEX 450 trim


CRI ≥ 80 · 220-240 V · DALI 1 ADDR. · IP50 · X-PERT

OPAL pure white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
23.2 W	3000 K	2840 lm	122 lm/W	0 6 3 - 3 2 4 8 5 ◆ 7 O
	4000 K	3010 lm	130 lm/W	0 6 3 - 3 2 4 8 6 ◆ 7 O







SONO FLEX 600 trim

CRI ≥ 80 · 220-240 V · DALI 1 ADDR. · IP50 · X-PERT

OPAL pure white, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
42.0 W	3000 K	5410 lm	129 lm/W	0 6 3 - 3 2 5 8 5 ◆ 7 O
	4000 K	5730 lm	136 lm/W	0 6 3 - 3 2 5 8 6 ◆ 7 O

Order options

CONTROL ◆	
non DIM	1
DALI-2	3

COLOUR	
pure white	RAL 9010

Mounting accessories



CONCRETE INSTALLATION HOUSING

TYPE	Ø·H (mm)	ORDER CODE
for SONO FLEX 350	364·107	0 6 3 - 2 2 3 8 1 0 0
for SONO FLEX 450	464·107	0 6 3 - 2 2 4 8 1 0 0
for SONO FLEX 600	614·107	0 6 3 - 2 2 5 8 1 0 0

Mounting tools accessories

DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0

Volksschule Erlaaer

Austria

Architect
ARGE Architekten
Kronaus – Mitterer/
Vasko & Partner

Photographer
Romana Fürnkranz
Architekturfotografie
Wien



Used products



SONO FLEX
recessed

No liability is assumed for
typographical or printing errors.
© XAL GmbH · Auer-Welsbach-
Gasse 36 · 8055 Graz · Austria ·
www.xal.com





LKH Graz Stroke Unit

Austria

Architect
Architekturbox
Eberndorf

Lighting Design
XAL

Photographer
Kurt Kuball



Used products



SONO FLEX recessed



RECOVER

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



