


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
up to ↓ 9,370 lm / ↑ 4,370 lm
up to 138 lm/W
L80 / 50000 h, L90 / 50000 h
Cover: Microprismatic
DALI-2
IP40

Types



Colours

Light distributions

TASK round


suspended

EN Round luminaire housing in aluminium; ultra low-profile design (only 15 mm); surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; incl. feeder cable or with height adjustable rod suspension (chrome), feed in rod; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; optional: indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; canopy for through wiring; sound absorbing accessories available

DE Runder Leuchtenkörper aus Aluminium; extrem flache Bauform (nur 15 mm); Oberfläche pulverbeschichtet; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung an der Leuchte; inkl. Einspeiseleitung oder mit kürzbarer Pendelrohrabhängung (chrom), Einspeiseleitung in Pendelrohr; direkte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach unten gelenkt; Lichtlenkung mittels hochreflektierenden Reflektormaterials; optional: Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom und maximale Deckenaufhellung; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung; schallabsorbierendes Zubehör erhältlich



DiiA® standards
251, 252, 253




DIN EN 12464-1
UGR ≤ 19



direct / indirect
illumination





acoustic
elements



CRI ≥ 98
XPECTRUM
(optional)





TASK 450 round suspended

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | IP 40 | X-PERT | X-PERT


MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
16.0 W	3000 K	1750 lm	109 lm/W	0 5 9 - 0 ♁ 4 1 0 3 ◪ P
	4000 K	1860 lm	116 lm/W	0 5 9 - 0 ♁ 4 1 1 3 ◪ P

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
37.0 W	3000 K	↧2710/↥1460 lm	113 lm/W	0 5 9 - 0 ♁ 6 1 0 3 ◪ P
	4000 K	↧2880/↥1550 lm	120 lm/W	0 5 9 - 0 ♁ 6 1 1 3 ◪ P





TASK 600 round suspended

CRI ≥ 90 | UGR ≤ 16 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | IP 40 | X-PERT | X-PERT


MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.6 W	3000 K	3470 lm	117 lm/W	0 5 9 - 0 ♁ 4 2 0 3 ◪ P
	4000 K	3690 lm	125 lm/W	0 5 9 - 0 ♁ 4 2 1 3 ◪ P

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
44.0 W	3000 K	↧3470/↥1770 lm	119 lm/W	0 5 9 - 0 ♁ 6 2 0 3 ◪ P
	4000 K	↧3690/↥1880 lm	127 lm/W	0 5 9 - 0 ♁ 6 2 1 3 ◪ P





TASK 900 round suspended

CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | 1-2 ADDR. | IP 40 | X-PERT | X-PERT

MICROPRISMATIC | DIRECT CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
51.0 W	3000 K	6630 lm	130 lm/W	0 5 9 - 0 ♁ 4 3 0 3 ◪ K
	4000 K	7060 lm	138 lm/W	0 5 9 - 0 ♁ 4 3 1 3 ◪ K

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
100.0 W	3000 K	↧8800/↥4110 lm	129 lm/W	0 5 9 - 0 ♁ 6 3 0 3 ◪ K
	4000 K	↧9370/↥4370 lm	137 lm/W	0 5 9 - 0 ♁ 6 3 1 3 ◪ K

Order options

MOUNTING ♁		COLOUR ◪	
cable 1500 mm	2	pure white RAL 9010	7
rod 1000 mm	4	jet black RAL 9005	8
		special colours	X