



TUBO 60

suspended


EN Supporting profile in extruded aluminium; end cap in aluminium; surface powder coated; suspended luminaire with cable suspension; height adjustment without tools; incl. feeder cable; light control via high quality lens system for maximum, homogeneous illumination; optionally cylindr. HPO (High Performance Opal) cover or clear, cylindrical cover with linear prismatic optic; energy-efficient LEDs with very good colour rendering

DE Tragprofil aus Aluminiumstrangpressprofil; Enddeckel aus Aluminium; Oberfläche pulverbeschichtet; Pendelleuchte mit Seilabhängung; werkzeuglose Höhenverstellung; inkl. Einspeiseleitung; Lichtlenkung mittels hochwertiger Linsenoptik für maximale, homogene Ausleuchtung; wahlweise zylindr. HPO (High Performance Opal) Abdeckung, oder klare, zylindrische Abdeckung mit Linearprismenoptik; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM
 (initial MacAdam)
 up to 3,280 lm/m
 up to 142 lm/W
 L90 / 50000 h
 DALI-2
 Clear Cover, High Performance
 Opal
 IP20

Types



Colour




Light distributions




driver
integrated




system solution



uniform
illumination




TUBO 60 opal suspended



OPAL DALI-2

| SYSTEM | LENGTH | COLOUR TEMP. | CRI ≥ | LUM. FLUX | EFFICACY | ORDER CODE | | |
|--------|---------|--------------|---------|-----------|----------|---|----------|---|
| 13.9 W | 625 mm | 3000 K | 80 | 1700 lm | 122 lm/W | 0 5 8 - 3 2 1 2 5 3 <input checked="" type="checkbox"/> O | | |
| | | | 90 | 1480 lm | 106 lm/W | 0 5 8 - 3 2 1 2 0 3 <input checked="" type="checkbox"/> O | | |
| | | 4000 K | 80 | 1810 lm | 130 lm/W | 0 5 8 - 3 2 1 2 6 3 <input checked="" type="checkbox"/> O | | |
| | | | 90 | 1480 lm | 106 lm/W | 0 5 8 - 3 2 1 2 1 3 <input checked="" type="checkbox"/> O | | |
| | | 27.9 W | 1210 mm | 3000 K | 80 | 3400 lm | 122 lm/W | 0 5 8 - 3 2 1 4 5 3 <input checked="" type="checkbox"/> O |
| | | | | | 90 | 2960 lm | 106 lm/W | 0 5 8 - 3 2 1 4 0 3 <input checked="" type="checkbox"/> O |
| 4000 K | 80 | | | 3620 lm | 130 lm/W | 0 5 8 - 3 2 1 4 6 3 <input checked="" type="checkbox"/> O | | |
| | 90 | | | 2960 lm | 106 lm/W | 0 5 8 - 3 2 1 4 1 3 <input checked="" type="checkbox"/> O | | |
| 34.0 W | 1500 mm | 3000 K | 80 | 4220 lm | 124 lm/W | 0 5 8 - 3 2 1 5 5 3 <input checked="" type="checkbox"/> O | | |
| | | | 90 | 3670 lm | 108 lm/W | 0 5 8 - 3 2 1 5 0 3 <input checked="" type="checkbox"/> O | | |
| | | 4000 K | 80 | 4490 lm | 132 lm/W | 0 5 8 - 3 2 1 5 6 3 <input checked="" type="checkbox"/> O | | |
| | | | 90 | 3670 lm | 108 lm/W | 0 5 8 - 3 2 1 5 1 3 <input checked="" type="checkbox"/> O | | |
| | | 54.0 W | 2375 mm | 3000 K | 80 | 6740 lm | 125 lm/W | 0 5 8 - 3 2 1 8 5 3 <input checked="" type="checkbox"/> O |
| | | | | | 90 | 5870 lm | 109 lm/W | 0 5 8 - 3 2 1 8 0 3 <input checked="" type="checkbox"/> O |
| 4000 K | 80 | | | 7170 lm | 133 lm/W | 0 5 8 - 3 2 1 8 6 3 <input checked="" type="checkbox"/> O | | |
| | 90 | | | 5870 lm | 109 lm/W | 0 5 8 - 3 2 1 8 1 3 <input checked="" type="checkbox"/> O | | |




TUBO 60 ribbed suspended



CLEAR COVER WITH LINEAR PRISMATIC OPTIC DALI-2

| SYSTEM | LENGTH | COLOUR TEMP. | CRI ≥ | LUM. FLUX | EFFICACY | ORDER CODE | | |
|--------|---------|--------------|---------|-----------|----------|---|----------|---|
| 13.9 W | 625 mm | 3000 K | 80 | 1820 lm | 131 lm/W | 0 5 8 - 5 2 1 2 5 3 <input checked="" type="checkbox"/> C | | |
| | | | 90 | 1580 lm | 114 lm/W | 0 5 8 - 5 2 1 2 0 3 <input checked="" type="checkbox"/> C | | |
| | | 4000 K | 80 | 1940 lm | 140 lm/W | 0 5 8 - 5 2 1 2 6 3 <input checked="" type="checkbox"/> C | | |
| | | | 90 | 1580 lm | 114 lm/W | 0 5 8 - 5 2 1 2 1 3 <input checked="" type="checkbox"/> C | | |
| | | 27.9 W | 1210 mm | 3000 K | 80 | 3640 lm | 130 lm/W | 0 5 8 - 5 2 1 4 5 3 <input checked="" type="checkbox"/> C |
| | | | | | 90 | 3170 lm | 114 lm/W | 0 5 8 - 5 2 1 4 0 3 <input checked="" type="checkbox"/> C |
| 4000 K | 80 | | | 3870 lm | 139 lm/W | 0 5 8 - 5 2 1 4 6 3 <input checked="" type="checkbox"/> C | | |
| | 90 | | | 3170 lm | 114 lm/W | 0 5 8 - 5 2 1 4 1 3 <input checked="" type="checkbox"/> C | | |
| 34.0 W | 1500 mm | 3000 K | 80 | 4510 lm | 133 lm/W | 0 5 8 - 5 2 1 5 5 3 <input checked="" type="checkbox"/> C | | |
| | | | 90 | 3930 lm | 116 lm/W | 0 5 8 - 5 2 1 5 0 3 <input checked="" type="checkbox"/> C | | |
| | | 4000 K | 80 | 4800 lm | 141 lm/W | 0 5 8 - 5 2 1 5 6 3 <input checked="" type="checkbox"/> C | | |
| | | | 90 | 3930 lm | 116 lm/W | 0 5 8 - 5 2 1 5 1 3 <input checked="" type="checkbox"/> C | | |
| | | 54.0 W | 2375 mm | 3000 K | 80 | 7210 lm | 134 lm/W | 0 5 8 - 5 2 1 8 5 3 <input checked="" type="checkbox"/> C |
| | | | | | 90 | 6280 lm | 116 lm/W | 0 5 8 - 5 2 1 8 0 3 <input checked="" type="checkbox"/> C |
| 4000 K | 80 | | | 7680 lm | 142 lm/W | 0 5 8 - 5 2 1 8 6 3 <input checked="" type="checkbox"/> C | | |
| | 90 | | | 6280 lm | 116 lm/W | 0 5 8 - 5 2 1 8 1 3 <input checked="" type="checkbox"/> C | | |



Order options

| COLOUR | |
|---------------------|---|
| pure white RAL 9010 | 7 |
| jet black RAL 9005 | 8 |

Office, Amsterdam


Netherlands

Architect
MVSA Architects

Photographer
Kris Dekeijser



Used products



TUBO 60 suspended

