


Quickinfo

3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 19
up to ↓ 4,370 lm / ↑ 9,320 lm
up to 136 lm/W
L90 / 50000 h
Loxone Air / ESSENTIAL sensor, Loxone Air / touch DIM on pole, stand alone ESSENTIAL sensor, touch DIM on pole
Microprismatic
IP20

Types



Colours



Light distributions



TASK

free standing

EN Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

DE Stehleuchte mit rechteckigem Leuchtenkopf aus Aluminium und abgerundeten Kanten; extrem flache Bauform (nur 15 mm); Standrohr rechteckig; Standfuß mit Ausnehmung für Tischfuß; Oberfläche pulverbeschichtet; direkt/indirekte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach oben und unten gelenkt; optional: Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom; optional: Indirektlichtanteil mit eigenen, schräg gerichteten Platinen für asymmetrische Abstrahlcharakteristik; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; inkl. Anschlussleitung (3m) mit Schutzkontaktstecker



suitable for double workstation




SENSE sensor on request



lighting control by touch DIM on pole




tunable white 2700 – 6500 K



CRI ≥ 98 XPECTRUM (optional)





TASK free standing u-shape

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 3000 | 220-240 V | X-PERT | X-PERT | presence | brightness

MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↧4100/↥3350 lm	111 lm/W	059-29430 ◆ Z
	4000 K	↧4370/↥3560 lm	118 lm/W	059-29431 ◆ Z


MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↧2400/↥7330 lm	128 lm/W	059-29420 ◆ Z
	4000 K	↧2550/↥7800 lm	136 lm/W	059-29421 ◆ Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↧1900/↥8630 lm	112 lm/W	059-29410 ◆ Z
	4000 K	↧2030/↥9320 lm	121 lm/W	059-29411 ◆ Z





TASK free standing t-shape

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 3000 | 220-240 V | X-PERT | X-PERT | presence | brightness

MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↧4100/↥3350 lm	111 lm/W	059-29530 ◆ Z
	4000 K	↧4370/↥3560 lm	118 lm/W	059-29531 ◆ Z

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↧2400/↥7330 lm	128 lm/W	059-29520 ◆ Z
	4000 K	↧2550/↥7800 lm	136 lm/W	059-29521 ◆ Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↧1900/↥8630 lm	112 lm/W	059-29510 ◆ Z
	4000 K	↧2030/↥9320 lm	121 lm/W	059-29511 ◆ Z

Order options

CONTROL ◆	
touch DIM on pole	5
stand alone ESSENTIAL sensor	7
Loxone Air / ESSENTIAL sensor	S
Loxone Air / touch DIM on pole	T

COLOUR ◪	
white aluminium RAL 9006	6
pure white RAL 9010	7
jet black RAL 9005	8
special colours	X

Office OMV, Vienna

Austria

Photographer
Kurt Kuball



Used products



TASK free standing

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com









