

## TASK

free standing


**EN** Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

**DE** Stehleuchte mit rechteckigem Leuchtenkopf aus Aluminium und abgerundeten Kanten; extrem flache Bauform (nur 15mm); Standrohr rechteckig; Standfuß mit Ausnehmung für Tischfuß; Oberfläche pulverbeschichtet; direkt/indirekte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach oben und unten gelenkt; optional: Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom; optional: Indirektlichtanteil mit eigenen, schräg gerichteten Platinen für asymmetrische Abstrahlcharakteristik; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; inkl. Anschlussleitung (3m) mit Schutzkontaktstecker

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  90 / 3 SDCM (initial MacAdam)  
 UGR  $\leq$  10, UGR  $\leq$  13, UGR  $\leq$  19  
 up to ↓ 4,370 lm / ↑ 9,320 lm  
 up to 136 lm/W  
 L90 / 50000 h  
 Loxone Air / ESSENTIAL sensor,  
 Loxone Air / touch DIM on pole,  
 stand alone ESSENTIAL sensor,  
 touch DIM on pole  
 Microprismatic  
 IP20

### Types



### Colour



### Light distributions




suitable for  
double  
workstation




SENSE sensor  
on request



lighting control  
by touch DIM on  
pole



tunable white  
2700 – 6500 K



CRI  $\geq$  98  
XPECTRUM  
(optional)




### TASK free standing u-shape



#### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↓4100/↑3350 lm	111 lm/W	0 5 9 - 2 9 4 3 0 <input checked="" type="checkbox"/> Z
	4000 K	↓4370/↑3560 lm	118 lm/W	0 5 9 - 2 9 4 3 1 <input checked="" type="checkbox"/> Z



#### MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↓2400/↑7330 lm	128 lm/W	0 5 9 - 2 9 4 2 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2550/↑7800 lm	136 lm/W	0 5 9 - 2 9 4 2 1 <input checked="" type="checkbox"/> Z

#### MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↓1900/↑8630 lm	112 lm/W	0 5 9 - 2 9 4 1 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2030/↑9320 lm	121 lm/W	0 5 9 - 2 9 4 1 1 <input checked="" type="checkbox"/> Z




### TASK free standing t-shape



#### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
67.0 W	3000 K	↓4100/↑3350 lm	111 lm/W	0 5 9 - 2 9 5 3 0 <input checked="" type="checkbox"/> Z
	4000 K	↓4370/↑3560 lm	118 lm/W	0 5 9 - 2 9 5 3 1 <input checked="" type="checkbox"/> Z



#### MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
76.0 W	3000 K	↓2400/↑7330 lm	128 lm/W	0 5 9 - 2 9 5 2 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2550/↑7800 lm	136 lm/W	0 5 9 - 2 9 5 2 1 <input checked="" type="checkbox"/> Z

#### MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
94.0 W	3000 K	↓1900/↑8630 lm	112 lm/W	0 5 9 - 2 9 5 1 0 <input checked="" type="checkbox"/> Z
	4000 K	↓2030/↑9320 lm	121 lm/W	0 5 9 - 2 9 5 1 1 <input checked="" type="checkbox"/> Z

#### Order options

CONTROL		COLOUR	
Loxone Air / ESSENTIAL sensor	S	white aluminium RAL 9006	6
Loxone Air / touch DIM on pole	T	pure white RAL 9010	7
touch DIM on pole	5	jet black RAL 9005	8
stand alone ESSENTIAL sensor	7	special colours	X

# Office OMV, Vienna

Austria

**Photographer**  
Kurt Kuball



## Used products



## TASK free standing

