



## PABLO shutter / iris / gobo


**EN** Track light made of die-cast aluminium; surface powder coated; 360° rotatable and 310° tiltable; converter in spotlight housing; COB (Chip on Board) technology - maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; contour spotlight for precise rectangular or round shape; easy adjustment by 4 shading elements or by iris-shaped shade made of stainless steel; incl. high quality bi-convex glass lens; sharp object focusing through adjustable lens; focus using rubber adjustment ring on spotlight head; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation optionally without tools by means of knurled screw or set screw (screwdriver required); point outlet, either in surface mounted housing or recessed housing, available as an accessory

**DE** Strahlschiene Strahler aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; 360° dreh- und 310° schwenkbar; Konverter im Strahlergehäuse; COB (Chip on Board) Technologie - höchste Effizienz; keine Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Konturstrahler für exakte rechteckige oder runde Formgebung; einfache Einstellung durch 4 Abschattenelemente oder durch irisförmige Abschatter aus Edelstahl; inkl. hochwertiger bikonvexer Glaslinse; scharfe Objekt-Fokussierung durch justierbare Linse; Fokussierung mittels gummiertem Verstellring am Strahlerkopf; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Strahlschiene; Adapter-Fixierung wahlweise werkzeuglos mittels Rändel- oder Feststellschraube (Schraubendreher erforderlich); Punktauslass, wahlweise in Anbaugeschäule bzw. Einbaugeschäule, als Zubehör erhältlich

### Quickinfo

3000 K, 4000 K  
 CRI ≥ 95 / 2 SDCM (initial MacAdam)  
 up to 17 lm/W  
 L85 / 50000h  
 DALI-2, DIM POTI  
 IP20

### Types



### Colour



compatible with  
 MOVE IT PRO  
 45



DiiA® standards  
 251, 252, 253



360° rotatable,  
 310° tiltable



shutter / iris /  
 gobo



DIM POTI /  
 rotation lock




## PABLO shutter track



31°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.0 W	3000 K	201 lm	14 lm/W	1 8 0 - 5 3 8 0 0
	4000 K	220 lm	16 lm/W	1 8 0 - 5 3 8 0 1
23.0 W	3000 K	298 lm	13 lm/W	1 8 0 - 5 3 8 1 0
	4000 K	327 lm	14 lm/W	1 8 0 - 5 3 8 1 1




## PABLO iris track




32°, CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.0 W	3000 K	210 lm	15 lm/W	1 8 0 - 5 4 8 0 0
	4000 K	231 lm	17 lm/W	1 8 0 - 5 4 8 0 1
23.0 W	3000 K	312 lm	14 lm/W	1 8 0 - 5 4 8 1 0
	4000 K	343 lm	15 lm/W	1 8 0 - 5 4 8 1 1




## Planning Information

### PABLO shutter




possible shapes of illumination

### PABLO iris



possible shapes of illumination

### Illumination size



A (mm)	H (mm)	Ø (mm)
1000	396	560
2000	792	1120
3000	1188	1680

## Mounting accessories (optional)

RECESSED HOUSING / POINT OUTLET ceiling thickness, 1-30 mm

Ø-H (mm)	ORDER CODE
151-60	1 8 6 - 0 7 2 2 7

## Order options

MOUNTING	8	CONTROL	3	COLOUR	7
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8



**SURFACE HOUSING / POINT OUTLET**

**Ø-H (mm)**  
120-32

**ORDER CODE**

1 8 6 - 0 7 2 2 8

**Order options**

<b>MOUNTING</b>	<input checked="" type="checkbox"/>	<b>CONTROL</b>	<input checked="" type="checkbox"/>	<b>COLOUR</b>	<input checked="" type="checkbox"/>
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8