




Quickinfo

6500 K
 up to 217 lm/W
 DALI-2 ESSENTIAL sensor,
 DALI-2 SENSE sensor
 front IP20, IP40, back IP20

Types



Colour



Mounting set



SASSO 60 round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement


DE Runder Einsatz (Notlicht bzw. Sensor); werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand); Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; LED Notlicht-Einsatz: 3 Varianten mit verschiedenen Testmöglichkeiten - Basic mit Prüftaste, Selbsttest mit Status-LED oder Pro DALI mit Überwachung über DALI; Sensor mit DALI-2 Steuerung: 2 Varianten - Basic mit Helligkeits- und Anwesenheitssensor oder Pro mit zusätzlicher Temperatur-, Luftfeuchtigkeits-, Luftqualitäts- und Lärmpegelmessung



quick mounting
 in soft acoustic
 ceilings



SASSO 60 round sensor essential



DALI-2 ESSENTIAL sensor

COLOUR

jet black

traffic white

ORDER CODE

0 4 8 - 2 6 9 3 1 1 1

0 4 8 - 2 6 9 3 1 1 7



SASSO 60 round sensor sense



DALI-2 SENSE sensor

COLOUR

jet black

traffic white

ORDER CODE

0 4 8 - 2 6 9 3 1 2 1

0 4 8 - 2 6 9 3 1 2 7



SASSO 60 round emergency light



3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 1 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses



3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 2 <input checked="" type="checkbox"/>

incl. 3 interchangeable lenses

3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS 21°-149°x150°, CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W	6500 K	217 lm	217 lm/W	0 4 8 - 2 6 9 3 2 3 <input checked="" type="checkbox"/>


incl. 3 interchangeable lenses

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017

Mounting accessories (required)

		MOUNTING SET trimless for plasterboard ceilings		
COLOUR	PLASTERBOARD CEILING THICKNESS	Ø-H (mm)	ORDER CODE	
traffic white	12.5/15/25 mm	73-29	0 4 8 - 2 6 9 6 1 1 7	
for SASSO 60 round SPIO 60 downlight				





 73
 60*/115**
 non DIM
 120
 DALI-2
 145
 loop through
 function
 * SASSO 60
 ** SPIO 60

		MOUNTING SET trimless for soft acoustic ceilings		
COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE	
traffic white	25-40 mm	80-25	0 4 8 - 2 6 9 6 1 9 7	





 74
 120
 non DIM
 120
 DALI-2
 145
 loop through
 function

		MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm		
COLOUR		Ø-H (mm)	ORDER CODE	
traffic white		80-27	0 4 8 - 2 6 9 6 3 9 7	
jet black		80-27	0 4 8 - 2 6 9 6 3 9 8	




 74
 100
 non DIM
 100
 DALI-2
 125
 loop through
 function


		MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm		
COLOUR		Ø-H (mm)	ORDER CODE	
traffic white		80-40	0 4 8 - 2 6 9 6 3 1 7	
jet black		80-40	0 4 8 - 2 6 9 6 3 1 8	



 73
 60
 non DIM
 100
 DALI-2
 125
 loop through
 function

Mounting accessories (optional)

		EXPOSED CONCRETE MOUNTING HOUSING		
COLOUR		L-W-H (mm)	ORDER CODE	
white aluminium		230-230-162	0 4 8 - 2 6 9 5 2 1 0	

		PRIMED CONCRETE MOUNTING HOUSING		
L-W-H (mm)			ORDER CODE	
614-307-120			0 4 8 - 2 6 9 5 1 1 0	
order mounting set separately				

Mounting tools accessories (optional)

		MOUNTING TOOL for soft acoustic ceilings		
COLOUR		L-W-H (mm)	ORDER CODE	
traffic black		77-77-35	0 4 8 - 2 6 9 5 9 1 8	

Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
traffic white RAL 9016	7	traffic black	RAL 9017



Electrical accessories (optional)

REPLACEMENT ACCUPACK

TYPE

3h battery life

ORDER CODE

0 4 8 - 2 6 9 3 9 1 0

Order options

COLOUR

jet black RAL 9005

traffic white RAL 9016



COLOUR

white aluminium

traffic black

RAL 9006

RAL 9017