



Quickinfo

2700 K, 3000 K, 4000 K, colour warm dimming 2000 - 3000 K, tunable white 1800 - 3000 K, tunable white 2700 - 6500 K
CRI ≥ 90, CRI ≥ 92, CRI ≥ 95 / 3 SDCM (initial MacAdam), 4 SDCM (initial MacAdam)
UGR ≤ 19, UGR ≤ 22
up to 105 lm/W
L70 / 50000 h, L80 / 50000 h, L85 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours

Mounting set

Light distributions

SASSO PRO 100 adjustable offset round

recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; surface powder coated; light inset rotatable and tiltable; offset lighting level; optical attachments available as accessories; high-quality reflector with spherical facet effect design, precise radiation characteristics with different beam angles; installed and exchanged without tools; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler aus Aluminiumdruckguss; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche pulverbeschichtet; Lichteinsatz dreh- und schwenkbar; zurückversetzte Leuchtenebene; optische Aufsätze sind als Zubehör erhältlich; hochwertiger Reflektor mit sphärischer Facettenoptik, präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; werkzeuglos einsetz- bzw. austauschbar; COB (Chip on Board) Technologie für höchste Effizienz; keine Bildung von Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe



360° rotatable, 35° tiltable



Colour Warm Dimming 2000 – 3000 K



tunable white 1800 – 3000 K or 2700 – 6500 K





SASSO PRO 100 adjustable

35° 360° | CRI ≥ 95 | UGR ≤ 19 | cd/m² ≤3000 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SPOT 17°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	048-241040 S
	3000 K	1410 lm	96 lm/W	048-241050 S
	4000 K	1490 lm	101 lm/W	048-241060 S
27.0 W	2700 K	2170 lm	80 lm/W	048-241240 S
	3000 K	2270 lm	84 lm/W	048-241250 S
	4000 K	2400 lm	89 lm/W	048-241260 S

MEDIUM 24°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	048-241040 M
	3000 K	1410 lm	96 lm/W	048-241050 M
	4000 K	1490 lm	101 lm/W	048-241060 M
27.0 W	2700 K	2170 lm	80 lm/W	048-241240 M
	3000 K	2270 lm	84 lm/W	048-241250 M
	4000 K	2400 lm	89 lm/W	048-241260 M

FLOOD 36°-38°,

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K, CRI ≥ 90	1360 lm	93 lm/W	048-241040 F
	3000 K, CRI ≥ 90	1420 lm	97 lm/W	048-241050 F
	4000 K, CRI ≥ 90	1500 lm	102 lm/W	048-241060 F
14.9 W	CWD, CRI ≥ 95	853 lm	57 lm/W	048-241113 F
27.0 W	2700 K, CRI ≥ 90	2190 lm	81 lm/W	048-241240 F
	3000 K, CRI ≥ 90	2280 lm	84 lm/W	048-241250 F
	4000 K, CRI ≥ 90	2420 lm	90 lm/W	048-241260 F

WIDE FLOOD 57°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
14.7 W	2700 K	1280 lm	87 lm/W	048-241040 W
	3000 K	1340 lm	91 lm/W	048-241050 W
	4000 K	1420 lm	97 lm/W	048-241060 W
27.0 W	2700 K	2070 lm	77 lm/W	048-241240 W
	3000 K	2160 lm	80 lm/W	048-241250 W
	4000 K	2280 lm	84 lm/W	048-241260 W

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8



SASSO PRO 100 adjustable high output



MEDIUM 26°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.0 W	3000 K	2790 lm	103 lm/W	0 4 8 - 2 4 1 3 5 ◪ M
	4000 K	2820 lm	104 lm/W	0 4 8 - 2 4 1 3 6 ◪ M

FLOOD 39°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
27.0 W	3000 K	2810 lm	104 lm/W	0 4 8 - 2 4 1 3 5 ◪ F
	4000 K	2840 lm	105 lm/W	0 4 8 - 2 4 1 3 6 ◪ F



SASSO PRO 100 adjustable (tunable white)



FLOOD 38°, CRI ≥ 92, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
21.0 W	tunable w., 1800 - 3000 K	1450 lm	69 lm/W	0 4 8 - 2 4 1 2 L 3 ◪ F
28.2 W	tunable w., 2700 - 6500 K	2180 lm	77 lm/W	0 4 8 - 2 4 1 2 D 3 ◪ F

Electrical mounting accessories (optional)



THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings, 12.5/15/25 mm

L·W·H (mm)	ORDER CODE
149·113·33	0 5 2 - 1 9 3 1 4 4 ◪

Order options

CONTROL ⬍		COLOUR ◪	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8



MOUNTING SET with trim for intermediate ceilings, 5-25 mm

Ø·H (mm)	ORDER CODE
112·43	052 - 193244

Mounting accessories (optional)



PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
240·400·130	052 - 191442 0

order mounting set separately

Optical accessories (optional)

HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
74·11	048 - 219131

LINEAR PRISMATIC LENS

Ø·H (mm)	ORDER CODE
74·11	048 - 219231



SNOOT

Ø·H (mm)	ORDER CODE
74·25	048 - 219111



SNOOT WITH HONEYCOMB LOUVER

Ø·H (mm)	ORDER CODE
74·25	048 - 219121

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

Health Resort Lanserhof Sylt

Germany

Architect
ingenhoven architects

Lighting Design
Tropp Lighting Design

Photographer
HGEsch



Used products



SASSO PRO 100 adjustable offset round recessed

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com





