




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
UGR ≤ 10, UGR ≤ 13, UGR ≤ 16, UGR ≤ 19, UGR ≤ 22, UGR ≤ 25
up to 93 lm/W
L90 / 100000 h
DALI-2, non DIM
IP20

Types



Colours



Inner colour



Light distributions



SASSO 60 base 2 lamps

ceiling

EN Cylindrical spotlight made of aluminium; light inset lacquered; housing powder coated; light inset rotatable and tiltable; double lamps; surface mounted housing in aluminium incl. converter; mounting plate with pre-assembled converter unit can be pre-mounted; luminaire housing can be attached without tools by interlock; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; luminaire for through wiring

DE Zylindrischer Strahler aus Aluminium; Lichteinsatz lackiert; Gehäuse pulverbeschichtet; Lichteinsatz dreh- und schwenkbar; zweiflammig; Anbaugehäuse aus Aluminium inkl. Konverter; Montageplatte mit vormontierter Konvertereinheit vorab montierbar; Leuchtenkörper mittels Verriegelung werkzeuglos aufsetzbar; präzise Abstrahlcharakteristik durch hochwertige Linsenoptik; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe; Leuchte für Weiterverdrahtung



glare control
(UGR ≤ 16)




easy mounting
no visible
screws



CRI ≥ 95 2
SDCM
(optional)





SASSO 60 base round adjustable 2 lamps ceiling

30° 360° | CRI ≥ 90 | 2 SDCM | UGR ≤ 10 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

SPOT 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.8 W	2700 K	2x735 lm	71 lm/W	048-314093 S
	3000 K	2x759 lm	73 lm/W	048-314003 S
	3500 K	2x775 lm	75 lm/W	048-314023 S
	4000 K	2x799 lm	77 lm/W	048-314013 S

The data values for the luminous flux of fraction may differ for specific order options by -8%. Luminous flux value refers to inner colour traffic white.

MEDIUM 27°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.5 W	2700 K	2x874 lm	85 lm/W	048-314093 M
	3000 K	2x907 lm	88 lm/W	048-314003 M
	3500 K	2x927 lm	90 lm/W	048-314023 M
	4000 K	2x946 lm	92 lm/W	048-314013 M

The data values for the luminous flux of fraction may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

FLOOD 40°-41°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.5 W	2700 K	2x831 lm	81 lm/W	048-314093 F
	3000 K	2x862 lm	84 lm/W	048-314003 F
	3500 K	2x880 lm	86 lm/W	048-314023 F
	4000 K	2x899 lm	88 lm/W	048-314013 F

The data values for the luminous flux of fraction may differ for specific order options by -14%. Luminous flux value refers to inner colour traffic white.

WIDE FLOOD 56°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.5 W	2700 K	2x876 lm	85 lm/W	048-314093 W
	3000 K	2x909 lm	89 lm/W	048-314003 W
	3500 K	2x928 lm	91 lm/W	048-314023 W
	4000 K	2x948 lm	93 lm/W	048-314013 W

The data values for the luminous flux of fraction may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black RAL 9005	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white RAL 9016	7
				gold dust RAL 260-M	9

Einfamilienhaus EFF, Austria

Austria

Architect
STUDIO WG3

Photographer
Heldentheater



Used products



SASSO 60 base 2 lamps ceiling

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com



