

MINO 100

suspended


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile for mounting available in advance; remaining luminaire components mounted without tools; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; spring clip attachment to the luminaire; freely positionable; incl. transparent feed; light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; energy-efficient LEDs with very good colour rendering

DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; Leuchtenprofil für Montage vorab lieferbar; restliche Leuchtenkomponenten werkzeuglos montierbar; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung an der Leuchte; Befestigung an der Leuchte mittels Federclips; frei positionierbar; inkl. transparenter Einspeiseleitung; Lichteinsatz bestehend aus hochreflektierend lackiertem Strangpressprofil für verbessertes Thermomanagement; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; mikroprismatische PMMA-Abdeckung inkl. Diffusorfolie zur Reduktion der Leuchtdichte bei homogener Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM (initial MacAdam)
 UGR ≤ 19
 up to 3,040 lm/m
 up to 143 lm/W
 L80 / 50000 h, L90 / 50000 h
 DALI-2, non DIM
 High Performance Opal, Microprismatic
 IP20

Types




Colour



Light distributions



DiiA® standards
 251, 252, 253




system solution



DIN EN 12464-1
 UGR ≤ 19




tunable white
 2700 – 6500 K
 (optional)



CRI ≥ 98
 XPECTRUM
 (optional)



MINO 100 suspended



MICROPRISMATIC | MID LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.9 W	888 mm	3000 K	1400 lm	118 lm/W	0 5 6 - 4 2 L 3 5 1 <input checked="" type="checkbox"/>
		4000 K	1480 lm	124 lm/W	0 5 6 - 4 2 L 3 6 1 <input checked="" type="checkbox"/>
15.3 W	1188 mm	3000 K	1860 lm	122 lm/W	0 5 6 - 4 2 L 4 5 1 <input checked="" type="checkbox"/>
		4000 K	1970 lm	129 lm/W	0 5 6 - 4 2 L 4 6 1 <input checked="" type="checkbox"/>
19.2 W	1488 mm	3000 K	2330 lm	121 lm/W	0 5 6 - 4 2 L 5 5 1 <input checked="" type="checkbox"/>
		4000 K	2470 lm	129 lm/W	0 5 6 - 4 2 L 5 6 1 <input checked="" type="checkbox"/>
30.0 W	2360 mm	3000 K	3730 lm	124 lm/W	0 5 6 - 4 2 L 8 5 1 <input checked="" type="checkbox"/>
		4000 K	3950 lm	132 lm/W	0 5 6 - 4 2 L 8 6 1 <input checked="" type="checkbox"/>

OPAL | MID LUMEN CRI ≥ 80, non DIM

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
11.9 W	888 mm	3000 K	1520 lm	128 lm/W	0 5 6 - 4 2 L 3 5 1 <input checked="" type="checkbox"/> H
		4000 K	1600 lm	134 lm/W	0 5 6 - 4 2 L 3 6 1 <input checked="" type="checkbox"/> H
15.3 W	1188 mm	3000 K	2020 lm	132 lm/W	0 5 6 - 4 2 L 4 5 1 <input checked="" type="checkbox"/> H
		4000 K	2140 lm	140 lm/W	0 5 6 - 4 2 L 4 6 1 <input checked="" type="checkbox"/> H
19.2 W	1488 mm	3000 K	2530 lm	132 lm/W	0 5 6 - 4 2 L 5 5 1 <input checked="" type="checkbox"/> H
		4000 K	2670 lm	139 lm/W	0 5 6 - 4 2 L 5 6 1 <input checked="" type="checkbox"/> H
30.0 W	2360 mm	3000 K	4040 lm	135 lm/W	0 5 6 - 4 2 L 8 5 1 <input checked="" type="checkbox"/> H
		4000 K	4280 lm	143 lm/W	0 5 6 - 4 2 L 8 6 1 <input checked="" type="checkbox"/> H

MICROPRISMATIC | HIGH LUMEN CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.6 W	888 mm	3000 K	2310 lm	112 lm/W	0 5 6 - 4 2 M 3 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		4000 K	2450 lm	119 lm/W	0 5 6 - 4 2 M 3 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
27.5 W	1188 mm	3000 K	3080 lm	112 lm/W	0 5 6 - 4 2 M 4 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		4000 K	3260 lm	119 lm/W	0 5 6 - 4 2 M 4 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
34.0 W	1488 mm	3000 K	3850 lm	113 lm/W	0 5 6 - 4 2 M 5 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		4000 K	4080 lm	120 lm/W	0 5 6 - 4 2 M 5 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
53.0 W	2360 mm	3000 K	6160 lm	116 lm/W	0 5 6 - 4 2 M 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
		4000 K	6520 lm	123 lm/W	0 5 6 - 4 2 M 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>


OPAL | HIGH LUMEN CRI ≥ 80

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
20.6 W	888 mm	3000 K	2510 lm	122 lm/W	0 5 6 - 4 2 M 3 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	2650 lm	129 lm/W	0 5 6 - 4 2 M 3 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
27.5 W	1188 mm	3000 K	3340 lm	121 lm/W	0 5 6 - 4 2 M 4 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	3540 lm	129 lm/W	0 5 6 - 4 2 M 4 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
34.0 W	1488 mm	3000 K	4180 lm	123 lm/W	0 5 6 - 4 2 M 5 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	4420 lm	130 lm/W	0 5 6 - 4 2 M 5 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
53.0 W	2360 mm	3000 K	6680 lm	126 lm/W	0 5 6 - 4 2 M 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H
		4000 K	7070 lm	133 lm/W	0 5 6 - 4 2 M 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H

Order options

CONTROL		COLOUR		COVER OPTION	
non DIM	1	white aluminium RAL 9006	G	microprismatic (glare reduced)	G
DALI-2	3	pure white RAL 9010	7	microprismatic	Z
		jet black RAL 9005	8		

Planning Information



MINO 100 suspended, 15.3 W,
4000 K, direct

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Suspension height	2.25 m

CALCULATION SURFACE -----

Surface dimensions	1.6 × 0.8 m
Surface height	0.75 m
Average illuminance (E_m)	> 500 lx
Uniformity (U_0)	> 0.6

GLARE EVALUATION

Table Classification X=4H | Y=8H | S=0.25H

UGR transversal	≤ 19
UGR axial	≤ 19

≥ 65° ≤ 3000 cd/m²

Order options

CONTROL		COLOUR		COVER OPTION	
non DIM	1	white aluminium RAL 9006	G	microprismatic (glare reduced)	G
DALI-2	3	pure white RAL 9010	7	microprismatic	Z
		jet black RAL 9005	8		

Bauer Group

Germany

Architect
designfunktion, Munich

Photographer
Martin Kreuzer
Photography



Used products



MINO 100 suspended



