



BASO 60 IP54

surface


^{EN} Luminaire housing from extruded aluminium profile, angular design; light-tight end caps in aluminium, no visible screws; surface powder coated; suitable for wall or ceiling mounting; luminaire profile (end caps come pre-assembled) can be pre-mounted; remaining luminaire components mounted without tools; closed light insert made of PMMA, consisting of converter unit and circuit board unit; light inset with screwed-on, thus maintenance-friendly, transparent end cap in PMMA; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering; IP67 socket connector system for easy and sealed electrical connection

^{DE} Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; lichtdicht abschließende Enddeckel aus Aluminium, keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; geeignet für Wand- oder Deckenmontage; Leuchtenprofil (Enddeckel werkseitig vormontiert) vorab montierbar; restliche Leuchtenkomponenten werkzeuglos montierbar; geschlossener Lichteinsatz aus PMMA, bestehend aus Konvertereinheit und Platineinheit; Lichteinsatz mit verschraubtem, dadurch wartungsfreundlichen, transparenten PMMA Enddeckel; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; IP67-Buchsen-Steckersystem für dichten elektrischen Anschluss

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 / 3 SDCM (initial MacAdam)
 up to 2,340 lm/m
 up to 130 lm/W
 L90 / 50000 h
 DALI-2
 High Performance Opal
 IP54

Types




Colour



Light distributions




quick
installation




system solution



dust & splash
water
protection (IP
54)



CRI ≥ 98
XPECTRUM
(optional)



BASO 60 ip54 surface



OPAL CRI ≥ 80, DALI-2

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|---------|--------------|-----------|----------|---|
| 10.8 W | 609 mm | 3000 K | 1320 lm | 122 lm/W | 8 4 5 - 4 1 2 2 5 3 <input checked="" type="checkbox"/> H |
| | | 4000 K | 1400 lm | 130 lm/W | 8 4 5 - 4 1 2 2 6 3 <input checked="" type="checkbox"/> H |
| 21.5 W | 1209 mm | 3000 K | 2640 lm | 123 lm/W | 8 4 5 - 4 1 2 4 5 3 <input checked="" type="checkbox"/> H |
| | | 4000 K | 2800 lm | 130 lm/W | 8 4 5 - 4 1 2 4 6 3 <input checked="" type="checkbox"/> H |
| 28.7 W | 1609 mm | 3000 K | 3520 lm | 123 lm/W | 8 4 5 - 4 1 2 5 5 3 <input checked="" type="checkbox"/> H |
| | | 4000 K | 3730 lm | 130 lm/W | 8 4 5 - 4 1 2 5 6 3 <input checked="" type="checkbox"/> H |
| 43.0 W | 2409 mm | 3000 K | 5280 lm | 123 lm/W | 8 4 5 - 4 1 2 8 5 3 <input checked="" type="checkbox"/> H |
| | | 4000 K | 5600 lm | 130 lm/W | 8 4 5 - 4 1 2 8 6 3 <input checked="" type="checkbox"/> H |



Order options

| COLOUR | <input checked="" type="checkbox"/> |
|---------------------|-------------------------------------|
| umbra grey RAL 7022 | D |
| pure white RAL 9010 | 7 |

Office BIG HQ, Copenhagen

Denmark


Architect
BIG Architects

Lighting Design
Anker & Co.

Photographer
Anker & Co.



Used products



BASO 60 IP54
surface

