

## HEX-O MODULE FLAT

ceiling single + group

**EN** Hexagonal acoustic element made of high quality, self-supporting, at least 50% recycled PET felt with sound absorbing properties; in the dimensions of the HEX-O luminaires - with reduced height; suitable for single or group installation; quick mounting system without tools; foreign fiber inclusions possible; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements; improvement of room acoustics through absorption and scattering of sound waves; up to absorption class A

**DE** Sechseckiges Akustikelement aus hochwertigem, selbsttragenden, mind. 50% recycelten PET-Filz mit schallabsorbierenden Eigenschaften; in Abmessungen der HEX-O Leuchten - mit reduzierter Höhe; geeignet für Einzel- und Gruppenmontage; werkzeugloses Schnellmontagesystem; Fremdfasereinschlüsse möglich; mit sämtlichen HEX-O ceiling und TRIG-O ceiling Leuchten und Akustikelementen kombinierbar; Verbesserung der Raumakustik durch Absorption und Schallstreuung; bis zu Absorberklasse A

### Quickinfo

PET felt  
up to absorption class A  
flame retardant version available

### Types



### Colour



modular system



easy mounting  
with one click



wide range of  
colours



### HEX-O module flat ceiling

A	B	C	<b>D</b>	E
$\alpha_w = 0.5$				
PET felt		0.7 NRC	0.69 SAA	

#### ACOUSTIC | SINGLE + GROUP

##### COLOUR

acoustic special colours

black

felt grey

marble grey

white

##### ORDER CODE


0 7 3 - 6 9 1 **L** 2 0 X

0 7 3 - 6 9 1 **L** 2 0 L

0 7 3 - 6 9 1 **L** 2 0 G

0 7 3 - 6 9 1 **L** 2 0 D


0 7 3 - 6 9 1 **L** 2 0 W




#### EQUIVALENT SOUND ABSORPTION AREA ( $A_{EQ} M^2$ )

W-L(mm)	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
650-750	0.03	0.1	0.27	0.4	0.5	0.43
866-1000	0.06	0.17	0.45	0.67	0.84	0.72

#### SOUND ABSORPTION COEFFICIENTS



#### Acoustic accessories (optional)



##### HEX-O ABSORBER 1000

##### COLOUR

marble grey

felt grey

black

white

acoustic special colours

##### L-W-H (mm)

1000-866-237

1000-866-237

1000-866-237

1000-866-237

1000-866-237

##### ORDER CODE

0 7 3 - 6 9 1 7 4 0 D

0 7 3 - 6 9 1 7 4 0 G

0 7 3 - 6 9 1 7 4 0 L

0 7 3 - 6 9 1 7 4 0 W

0 7 3 - 6 9 1 7 4 0 X

only in combination with HEX-O 750, MODULE 750 or MODULE FLAT 750; for acoustic data see xal.com

#### Order options

LENGTH	L
750 mm	6
1000 mm	7