



Quickinfo

3000 K, 4000 K, tunable white
2700 - 6500 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 19
up to 163 lm/W
L90 / 100000 h, L90 / 75000 h
DALI-2
Reflector
IP20

Types



Colours



Reflector



Light distributions



MITA square 200 / 360

recessed

EN Square luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory; suitable for ceiling thickness of 2-25 mm; surface powder coated; high-gloss reflector with faceted design; energy-efficient LEDs with very good colour rendering

DE Quadratischer Leuchtenkörper aus Aluminiumdruckguss; extrem schlanke Bauform; Einbauleuchte mit umlaufendem Rand; optional: Blindabdeckung zum Einlegen im Innenausschnitt als Zubehör erhältlich; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; hochglänzender Reflektor mit Facettenoptik; energieeffiziente LEDs mit sehr guter Farbwiedergabe




suitable for plasterboard or grid ceilings



DIN EN 12464-1
UGR ≤ 19



tunable white
2700 – 6500 K





MITA SQUARE 200 trim

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
13.4 W	tunable w.	90	chrome	1720 lm	128 lm/W	074-83140 3 R
			dark chr.	1230 lm	92 lm/W	074-83140 3 B
13.8 W	3000 K	80	chrome	2080 lm	151 lm/W	074-83145 3 R
			dark chr.	1490 lm	108 lm/W	074-83145 3 B
		90	chrome	1810 lm	131 lm/W	074-83140 3 R
			dark chr.	1300 lm	94 lm/W	074-83140 3 B
	4000 K	80	chrome	2220 lm	161 lm/W	074-83146 3 R
			dark chr.	1590 lm	115 lm/W	074-83146 3 B
		90	chrome	1810 lm	131 lm/W	074-83141 3 R
			dark chr.	1300 lm	94 lm/W	074-83141 3 B






MITA SQUARE 360 trim

TUNABLE WHITE | CRI ≥ 90 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT | X-PERT

REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
26.9 W	tunable w.	90	chrome	3440 lm	128 lm/W	074-83160 3 R
			dark chr.	2460 lm	91 lm/W	074-83160 3 B
29.4 W	3000 K	80	chrome	4500 lm	153 lm/W	074-83165 3 R
			dark chr.	3220 lm	110 lm/W	074-83165 3 B
		90	chrome	3920 lm	133 lm/W	074-83160 3 R
			dark chr.	2800 lm	95 lm/W	074-83160 3 B
	4000 K	80	chrome	4790 lm	163 lm/W	074-83166 3 R
			dark chr.	3430 lm	117 lm/W	074-83166 3 B
		90	chrome	3920 lm	133 lm/W	074-83161 3 R
			dark chr.	2800 lm	95 lm/W	074-83161 3 B
40.0 W	3000 K	80	chrome	5850 lm	146 lm/W	074-83265 3 R
			dark chr.	4190 lm	105 lm/W	074-83265 3 B
		90	chrome	5100 lm	128 lm/W	074-83260 3 R
			dark chr.	3650 lm	91 lm/W	074-83260 3 B
	4000 K	80	chrome	6230 lm	156 lm/W	074-83266 3 R
			dark chr.	4460 lm	112 lm/W	074-83266 3 B
		90	chrome	5100 lm	128 lm/W	074-83261 3 R
			dark chr.	3650 lm	91 lm/W	074-83261 3 B



Optical accessories

BLIND COVER square 200

ORDER CODE
074-89134 1

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8

BLIND COVER square 360

ORDER CODE
0 7 4 - 8 9 1 3 6 1

Order options

COLOUR	
traffic white RAL 9016	7
jet black RAL 9005	8