

LINEA

system


EN Luminaire housing and front cover from extruded aluminium profile, angular version; no visible screws; designed for continuous lighting systems, 90° angle connectors for flexible system design; surface powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; HPO (High Performance Opal) cover for uniform illumination; or with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); energy-efficient LEDs with very good colour rendering; optionally JUST 26 spotlight module can be installed

DE Leuchtenkörper und Frontabdeckung aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; ausgelegt für durchgehende Lichtsysteme, 90° Winkelverbinder für flexiblen Systemaufbau; Oberfläche pulverbeschichtet; geeignet für Wandmontage; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige direkt/indirekte Lichtverteilung; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; oder mit speziell berechneter, asymmetrischer Linse für homogene Beleuchtungsstärken (Montage wahlweise zur Boden- oder Deckenaufhellung); energieeffiziente LEDs mit sehr guter Farbwiedergabe; wahlweise JUST 26 Strahlereinsatz einsetzbar


Quickinfo

3000 K, 4000 K, tunable white
2700 - 5000 K
CRI \geq 90, CRI \geq 97 / 3 SDCM
(initial MacAdam)
up to ↓ 4,020 lm/↑ 4,770 lm
up to 125 lm/W
L85 / 50000 h, L95 / 50000 h
DALI-2, non DIM
High Performance Opal, High
Performance Opal / Asymmetric
IP20 / PC1 / 220-240 V

Types



Light distributions



CRI \geq 98
XPECTRUM
(optional)



LINEA wall system



OPAL / ASYMMETRIC CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|---------|--------------------------------|----------------|----------|---|
| 8.9 W | 306 mm | 3000 K | ↓428/±509 lm | 105 lm/W | 0 5 8 - 6 1 4 1 5 <input checked="" type="checkbox"/> A A |
| | | 4000 K | ↓472/±562 lm | 116 lm/W | 0 5 8 - 6 1 4 1 6 <input checked="" type="checkbox"/> A A |
| 17.6 W | 606 mm | 3000 K | ↓881/±1050 lm | 110 lm/W | 0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> A A |
| | | 4000 K | ↓972/±1160 lm | 121 lm/W | 0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> A A |
| 34.0 W | 1206 mm | 3000 K | ↓1760/±2090 lm | 113 lm/W | 0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> A A |
| | | 4000 K | ↓1940/±2310 lm | 125 lm/W | 0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> A A |
| 39.0 W | 1206 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2390 lm | 113 lm/W | 0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> A A |
| 68.0 W | 2406 mm | 3000 K | ↓3520/±4190 lm | 113 lm/W | 0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> A A |
| | | 4000 K | ↓3890/±4620 lm | 125 lm/W | 0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> A A |
| 76.0 W | 2406 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓4020/±4770 lm | 116 lm/W | 0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> A A |



OPAL / OPAL CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|---------|--------------------------------|----------------|----------|---|
| 8.9 W | 306 mm | 3000 K | ↓428/±428 lm | 96 lm/W | 0 5 8 - 6 1 4 1 5 <input checked="" type="checkbox"/> A H |
| | | 4000 K | ↓472/±472 lm | 106 lm/W | 0 5 8 - 6 1 4 1 6 <input checked="" type="checkbox"/> A H |
| 17.6 W | 606 mm | 3000 K | ↓881/±881 lm | 100 lm/W | 0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> A H |
| | | 4000 K | ↓972/±972 lm | 110 lm/W | 0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> A H |
| 34.0 W | 1206 mm | 3000 K | ↓1760/±1760 lm | 104 lm/W | 0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> A H |
| | | 4000 K | ↓1940/±1940 lm | 114 lm/W | 0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> A H |
| 39.0 W | 1206 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2010 lm | 103 lm/W | 0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> A H |
| 68.0 W | 2406 mm | 3000 K | ↓3520/±3520 lm | 104 lm/W | 0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> A H |
| | | 4000 K | ↓3890/±3890 lm | 114 lm/W | 0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> A H |
| 76.0 W | 2406 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓4020/±4020 lm | 106 lm/W | 0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> A H |




LINEA inner corner wall system



OPAL / ASYMMETRIC CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------|--------------------------------|----------------|----------|---|
| 34.0 W | 633 mm | 3000 K | ↓1760/±2090 lm | 113 lm/W | 0 5 8 - 6 1 1 1 5 <input checked="" type="checkbox"/> A A |
| | | 4000 K | ↓1940/±2310 lm | 125 lm/W | 0 5 8 - 6 1 1 1 6 <input checked="" type="checkbox"/> A A |
| 39.0 W | 633 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2390 lm | 113 lm/W | 0 5 8 - 6 1 1 1 D 3 <input checked="" type="checkbox"/> A A |



OPAL / OPAL CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------|--------------------------------|----------------|----------|---|
| 34.0 W | 633 mm | 3000 K | ↓1760/±1760 lm | 104 lm/W | 0 5 8 - 6 1 1 1 5 <input checked="" type="checkbox"/> A H |
| | | 4000 K | ↓1940/±1940 lm | 114 lm/W | 0 5 8 - 6 1 1 1 6 <input checked="" type="checkbox"/> A H |
| 39.0 W | 633 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2010 lm | 103 lm/W | 0 5 8 - 6 1 1 1 D 3 <input checked="" type="checkbox"/> A H |

Order options

| CONTROL | | COLOUR | | MOUNTING | |
|---------|---|---------------------|---|-----------------|---|
| non DIM | 1 | pure white RAL 9010 | 7 | spotlight left | B |
| DALI-2 | 3 | jet black RAL 9005 | 8 | spotlight right | C |




LINEA outer corner wall system



OPAL / ASYMMETRIC CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------|--------------------------------|----------------|----------|---|
| 34.0 W | 637 mm | 3000 K | ↓1760/±2090 lm | 113 lm/W | 0 5 8 - 6 1 1 2 5 <input checked="" type="checkbox"/> A A |
| | | 4000 K | ↓1940/±2310 lm | 125 lm/W | 0 5 8 - 6 1 1 2 6 <input checked="" type="checkbox"/> A A |
| 39.0 W | 637 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2390 lm | 113 lm/W | 0 5 8 - 6 1 1 2 D 3 <input checked="" type="checkbox"/> A A |



OPAL / OPAL CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|--------|--------------------------------|----------------|----------|---|
| 34.0 W | 637 mm | 3000 K | ↓1760/±1760 lm | 104 lm/W | 0 5 8 - 6 1 1 2 5 <input checked="" type="checkbox"/> A H |
| | | 4000 K | ↓1940/±1940 lm | 114 lm/W | 0 5 8 - 6 1 1 2 6 <input checked="" type="checkbox"/> A H |
| 39.0 W | 637 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2010 lm | 103 lm/W | 0 5 8 - 6 1 1 2 D 3 <input checked="" type="checkbox"/> A H |




LINEA 1 spotlight wall system



OPAL / OPAL | 1 SPOTLIGHT 30°, CRI ≥ 90

| SYSTEM | LENGTH | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|--------|---------|--------------------------------|----------------|----------|---|
| 17.6 W | 706 mm | 3000 K | ↓881/±881 lm | 100 lm/W | 0 5 8 - 6 1 4 2 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| | | 4000 K | ↓972/±972 lm | 110 lm/W | 0 5 8 - 6 1 4 2 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| 34.0 W | 1306 mm | 3000 K | ↓1760/±1760 lm | 104 lm/W | 0 5 8 - 6 1 4 4 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| | | 4000 K | ↓1940/±1940 lm | 114 lm/W | 0 5 8 - 6 1 4 4 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| 39.0 W | 1306 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓2010/±2010 lm | 103 lm/W | 0 5 8 - 6 1 4 4 D 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| 68.0 W | 2506 mm | 3000 K | ↓3520/±3520 lm | 104 lm/W | 0 5 8 - 6 1 4 8 5 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| | | 4000 K | ↓3890/±3890 lm | 114 lm/W | 0 5 8 - 6 1 4 8 6 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |
| 76.0 W | 2506 mm | ↓ tunable w./ ±2700 K - 5000 K | ↓4020/±4020 lm | 106 lm/W | 0 5 8 - 6 1 4 8 D 3 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> H |



spotlight 1 x 2,6 W / 159 lm only with 3000 K

Mounting accessories (optional)



END CAPS 1 pair

L-W-H (mm)
40-100-12

ORDER CODE
0 5 0 - 2 5 4 0 1 0



LINEAR CONNECTOR

TYPE
1 piece
10 pieces

L-W (mm)
60-38

ORDER CODE
0 5 0 - 2 5 5 1 1 0 0
0 5 0 - 2 5 5 1 1 0 0 · 1 0

Order options

| CONTROL | | COLOUR | | MOUNTING | |
|---------|---|---------------------|---|-----------------|---|
| non DIM | 1 | pure white RAL 9010 | 7 | spotlight left | B |
| DALI-2 | 3 | jet black RAL 9005 | 8 | spotlight right | C |

Electrical accessories (optional)**THROUGH WIRE**

| TYPE | ORDER CODE |
|--|-------------------|
| 3×1.5mm ² 10 pieces non DIM | 0 0 4 - 9 0 0 0 3 |
| 5×1.5mm ² 10 pieces DALI-2 | 0 0 4 - 9 0 0 0 5 |

Order options

| CONTROL | COLOUR | MOUNTING |
|----------------|-----------------------|-------------------|
| non DIM | 1 pure white RAL 9010 | 7 spotlight left |
| DALI-2 | 3 jet black RAL 9005 | 8 spotlight right |