




Quickinfo

3000 K, 4000 K
 CRI ≥ 90 / 3 SDCM (initial MacAdam)
 up to 2,510 lm/m
 up to 113 lm/W
 L80 / 50000 h
 DALI-2, non DIM
 High Performance Opal
 IP44

Types



Colour



End cap



Light distributions



STRETTA

wall

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; end caps powder coated in same colour as housing or brushed aluminium; suitable for wall mounting; with three sided light beam; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering


DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; Leuchtenprofil vorab montierbar; Enddeckel in Leuchtenfarbe pulverbeschichtet oder Aluminium gebürstet; geeignet für Wandmontage; mit dreiseitiger Lichtabstrahlung; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe



wall illumination



splash water protection (IP 44)



CRI ≥ 98 XPECTRUM




STRETTA wall



OPAL CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	0 5 7 - 0 1 3 2 5 <input checked="" type="checkbox"/> H
		4000 K	1480 lm	113 lm/W	0 5 7 - 0 1 3 2 6 <input checked="" type="checkbox"/> H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	0 5 7 - 0 1 3 3 5 <input checked="" type="checkbox"/> H
		4000 K	2220 lm	113 lm/W	0 5 7 - 0 1 3 3 6 <input checked="" type="checkbox"/> H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	0 5 7 - 0 1 3 4 5 <input checked="" type="checkbox"/> H
		4000 K	2950 lm	112 lm/W	0 5 7 - 0 1 3 4 6 <input checked="" type="checkbox"/> H




STRETTA wall | end caps aluminium



OPAL pure white, CRI ≥ 90

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
13.1 W	600 mm	3000 K	1340 lm	102 lm/W	0 5 7 - 0 1 3 2 5 <input checked="" type="checkbox"/> 2 H
		4000 K	1480 lm	113 lm/W	0 5 7 - 0 1 3 2 6 <input checked="" type="checkbox"/> 2 H
19.7 W	900 mm	3000 K	2010 lm	102 lm/W	0 5 7 - 0 1 3 3 5 <input checked="" type="checkbox"/> 2 H
		4000 K	2220 lm	113 lm/W	0 5 7 - 0 1 3 3 6 <input checked="" type="checkbox"/> 2 H
26.3 W	1200 mm	3000 K	2680 lm	102 lm/W	0 5 7 - 0 1 3 4 5 <input checked="" type="checkbox"/> 2 H
		4000 K	2950 lm	112 lm/W	0 5 7 - 0 1 3 4 6 <input checked="" type="checkbox"/> 2 H



Order options

CONTROL		COLOUR	
non DIM	1	pure white RAL 9010	7
DALI-2	3	jet black RAL 9005	8