


Quickinfo

3000 K, 4000 K
CRI ≥ 95 / 3 SDCM (initial MacAdam)
up to 99 lm/W
L80 / 50000 h, L85 / 50000 h
excl. driver
IP20

Types



Colours

Light distributions

MICRO 10

recessed

EN Round recessed spotlight in aluminium; surface lacquered; high quality lens system; precise radiation characteristic; energy-efficient LEDs with very good colour rendering; plug and play electrical connector system for toolless mounting; converter plug and play; converter separately available

DE Runder Einbaustrahler aus Aluminium; Oberfläche lackiert; hochwertige Linsenoptik; präzise Abstrahlcharakteristik; energieeffiziente LEDs mit sehr guter Farbwiedergabe; durchkontaktiertes elektrisches Stecksystem für werkzeuglose Montage; Konverter steckerfertig vorkonfektioniert; Konverter ist separat zu bestellen




CRI ≥ 95, R9 ≥ 90



MICRO 10 recessed

CRI ≥ 95 · UGR ≤ 16 · cd/m² ≤ 1500 · III · DALI-2 · CB · UL · X-PERT



SPOT 18°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
1.0 W, 350 mA	3000 K	61 lm	60 lm/W	0 1 1 - 8 1 0 0 0 1 ◪ S
1.1 W, 350 mA	4000 K	67 lm	63 lm/W	0 1 1 - 8 1 0 0 1 1 ◪ S

light inset incl. connection cable with socket 0.5 m

MEDIUM 30°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.9 W, 350 mA	3000 K	92 lm	97 lm/W	0 1 1 - 8 1 0 0 0 1 ◪ M
1.0 W, 350 mA	4000 K	100 lm	99 lm/W	0 1 1 - 8 1 0 0 1 1 ◪ M

light inset incl. connection cable with socket 0.5 m

FLOOD 39°, CRI ≥ 95, excl. driver

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
0.9 W, 350 mA	3000 K	93 lm	98 lm/W	0 1 1 - 8 1 0 0 0 1 ◪ F
1.0 W, 350 mA	4000 K	101 lm	99 lm/W	0 1 1 - 8 1 0 0 1 1 ◪ F

light inset incl. connection cable with socket 0.5 m

Electrical mounting accessories

EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

feeder length	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 1 2 0
2000 mm	0 1 1 - 9 2 2 1 1 4 0
4000 mm	0 1 1 - 9 2 2 1 1 8 0

Electrical accessories

POWER SUPPLY EU 350 mA

TYPE	L·W·H (mm)	ORDER CODE
non DIM	115·19·34	0 1 1 - 9 2 1 3 1 1 0
DALI-2	145·33·21	0 1 1 - 9 2 1 3 1 3 0

incl. power cable 2 m + connection cable with plug 1 m

POWER SUPPLY UL 350 mA, 42 W, 90-277 V AC, PC2

EFFICIENCY	L·W·H (mm)	ORDER CODE
η 89 %	131·43·30	0 1 1 - 9 2 7 3 1 1 0
η 89 %		0 1 1 - 9 2 9 3 1 1 0

CONNECTION CABLE 1 × open / 1 × top plug

FEEDER LENGTH	ORDER CODE
1000 mm	0 1 1 - 9 2 2 1 6 2 0

Order options

NOTE

Products from the Showcase Lighting range are excluded from returns.

COLOUR ◪

white aluminium RAL 9006	6
tar black RAL 9021	8

SPLITTER SERIAL

TYPE	L·W·H (mm)	ORDER CODE
3 × socket / 1 × plug	38·30·10	011-922830 0
6 × socket / 1 × plug	55·32·10	011-922860 0

Order options

NOTE

Products from the Showcase Lighting range are excluded from returns.