


## Quickinfo

3000 K, 4000 K
CRI ≥ 95 / 3 SDCM (initial MacAdam)
up to 18 lm/W
L80 / 50000 h, L85 / 50000 h
excl. driver
IP20

### Types




### Colours

### Light distributions

# **FINA SUPPORT** stadio

standing system

EN Miniature rectangular lamp made of aluminium; angular design; surface lacquered; plug and play electrical connector system for toolless mounting; different mechanical and electrical poles available; for flexible system design; equipped with miniature spotlight heads; spotlight heads rotatable and tiltable; high quality lens system; precise radiation characteristics with different beam angles; light inset rotatable; energy-efficient LEDs with very good colour rendering; converter plug and play; converter separately available

DE Miniatur Bügelleuchte aus Aluminium; kantige Bauform; Oberfläche lackiert; durchkontaktiertes elektrisches Stecksystem für werkzeuglose Montage; unterschiedliche mechanische und elektrische Poles verfügbar; für flexiblen Systemaufbau; bestückt mit Miniatur-Strahlerköpfen; Strahlerköpfe dreh- und schwenkbar; hochwertige Linsenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; Lichteinsatz drehbar; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Konverter steckerfertig vorkonfektioniert; Konverter ist separat zu bestellen



CRI ≥ 95, R9 ≥ 90




360° rotatable, 90° tiltable



easily replaceable






## **FINA SUPPORT** stadio 10 standing system

90° 360° | CRI ≥95 | 24V | DALI-2 | CB | UL | X-PERT

### SPOT 18°, CRI ≥ 95, excl. driver

| FIXTURE | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 4.4 W | 3000 K | 6x41 lm | 011-220301◪S |
| 4.7 W | 4000 K | 6x45 lm | 011-220311◪S |

Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions

### MEDIUM 30°, CRI ≥ 95, excl. driver

| FIXTURE | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 4.2 W | 3000 K | 6x55 lm | 011-220301◪M |
| 4.5 W | 4000 K | 6x60 lm | 011-220311◪M |


Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions

### FLOOD 39°, CRI ≥ 95, excl. driver

| FIXTURE | COLOUR TEMP. | LUM. FLUX | ORDER CODE |
|---|---|---|---|
| 4.2 W | 3000 K | 6x55 lm | 011-220301◪F |
| 4.5 W | 4000 K | 6x60 lm | 011-220311◪F |

Light inset incl. 1 electrical linear connector (UL version only); note the maximum allowed system power from the mounting instructions

## Planning Information




1 **L-SUPPORT SQUARE** mechanical

2 **T-SUPPORT SQUARE** mechanical / electrical

3 **L-SUPPORT SQUARE** mechanical / feeder

2 **Y-SUPPORT SQUARE** mechanical / electrical


3 **Y-SUPPORT SQUARE** mechanical / feeder

## Order options

| COLOUR | ◪ |
|---|---|
| white aluminium RAL 9006 | 6 |
| tar black RAL 9021 | 8 |


**NOTE**
Products from the Showcase Lighting range are excluded from returns.

## Electrical mounting accessories




### CONNECTION CABLE

| TYPE | ORDER CODE |
|---|---|
| 1 × open / 1 × DC plug | 0 1 1 - 9 2 2 2 6 2 0 |





### EXTENSION CABLE 1 × socket / 1 × plug, 350 mA

| feeder length | ORDER CODE |
|---|---|
| 1000 mm | 0 1 1 - 9 2 2 2 1 2 0 |
| 2000 mm | 0 1 1 - 9 2 2 2 1 4 0 |
| 4000 mm | 0 1 1 - 9 2 2 2 1 8 0 |


### FLEX CONNECTOR 0-83° electrical

| L·W (mm) | ORDER CODE |
|---|---|
| 33·6 | 0 1 1 - 9 2 2 5 4 0 0 |





### MOUNTING POLE L mechanical / feeder

| L (mm) | ORDER CODE |
|---|---|
| 180 | 0 1 1 - 9 1 2 W 1 3 ◪ |
| 200 | 0 1 1 - 9 1 2 W 2 3 ◪ |
| 300 | 0 1 1 - 9 1 2 W 3 3 ◪ |





### MOUNTING POLE T mechanical / electrical

| L·W (mm) | ORDER CODE |
|---|---|
| 180·31 | 0 1 1 - 9 1 2 2 1 2 ◪ |
| 200·31 | 0 1 1 - 9 1 2 2 2 2 ◪ |
| 300·31 | 0 1 1 - 9 1 2 2 3 2 ◪ |




### MOUNTING POLE Y mechanical / electrical


| L·W (mm) | ORDER CODE |
|---|---|
| 180·24 | 0 1 1 - 9 1 2 3 1 2 ◪ |
| 200·24 | 0 1 1 - 9 1 2 3 2 2 ◪ |
| 300·24 | 0 1 1 - 9 1 2 3 3 2 ◪ |




### MOUNTING POLE Y mechanical / feeder

| L·W (mm) | ORDER CODE |
|---|---|
| 180·24 | 0 1 1 - 9 1 2 3 1 3 ◪ |
| 200·24 | 0 1 1 - 9 1 2 3 2 3 ◪ |
| 300·24 | 0 1 1 - 9 1 2 3 3 3 ◪ |

## Mounting accessories




### MOUNTING POLE L mechanical

| L (mm) | ORDER CODE |
|---|---|
| 180 | 0 1 1 - 9 1 2 W 1 1 ◪ |
| 200 | 0 1 1 - 9 1 2 W 2 1 ◪ |
| 300 | 0 1 1 - 9 1 2 W 3 1 ◪ |

**Order options**

| WIDTH | W |
|---|---|
| 20 mm | 1 |
| 35 mm | 4 |
| 50 mm | 5 |
| 85 mm | 6 |

| WIDTH | W |
|---|---|
| 95 mm | 7 |
| 100 mm | 8 |

| COLOUR | ◪ |
|---|---|
| white aluminium RAL 9006 | 6 |
| tar black RAL 9021 | 8 |

**NOTE**

Products from the Showcase Lighting range are excluded from returns.

## Electrical accessories

**POWER SUPPLY 24V EU** PC2

| TYPE | INPUT VOLTAGE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|---|
| 18 W \| non DIM | 198-264 V AC | η 86 % | 130·43·30 | 011-921211 0 |
| 35 W \| non DIM | 198-264 V AC | η 86 % | 195·43·30 | 011-921222 0 |
| 60 W \| non DIM | 198-264 V AC | η 91 % | 220·43·30 | 011-921231 0 |
| 18 W \| DALI-2 | 198-264 V AC | η 84 % | 130·43·30 | 011-921213 0 |
| 35 W \| DALI-2 | 198-264 V AC | η 89 % | 195·43·30 | 011-921223 0 |
| 60 W \| DALI-2 | 198-240 V AC | η 93 % | 220·43·30 | 011-921233 0 |

incl. power cable 2m + connection cable with plug 1m

**POWER SUPPLY 24V UL** non DIM, 100-305 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 25 W | η 88 % | 147·40·32 | 011-927211 0 |
| 40 W | η 88 % | 147·40·32 | 011-927221 0 |
| 60 W | η 87 % | 176·45·32 | 011-927231 0 |

**POWER SUPPLY 24V UL incl. metalbox** non DIM, 100-305 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 25 W | η 88 % | 196·68·45 | 011-929211 0 |
| 40 W | η 88 % | 196·68·45 | 011-929221 0 |
| 60 W | η 87 % | 223·66·55 | 011-929231 0 |

**SYSTEM SPLITTER**

| TYPE | ORDER CODE |
|---|---|
| 3 way | 011-923830 0 |
| 6 way | 011-923860 0 |

**Order options**

**NOTE**
Products from the Showcase Lighting range are excluded from returns.

# Pole overview





## **L-SUPPORT** standing

EN Arranged linearly along the showcase table, FINA support System, electrically and mechanically connected via the L-Support Poles, ensures excellent illumination of the products or exhibits without restricting the view.

DE Lineare angeordnet entlang des Vitrinen Tisches sorgt FINA support System, elektrisch und mechanisch über die L-Support Pole verbunden, für eine hervorragende Ausleuchtung der Ware oder Exponate, ohne den Blick darauf einzuschränken.

---





## **T-SUPPORT** standing

EN The T-Support Pole of the FINA support system is primarily used for large display case when several light insets are combined and arranged in a row. The T-Support poles are used to connect them together electrically and mechanically.

DE Die T-Support Pole des FINA support Systems findet vor allem bei großen Vitrinenflächen ihren Einsatz, wenn mehrere Lichteinsätze kombiniert und aneinandergereiht werden. Mittels der T-Support Pole werden diese elektrisch und mechanisch miteinander verbunden.

---





## **Y-SUPPORT** standing

EN The Y-connectors of the FINA support system enable ideal illumination of the entire display case by allowing different insets to be mechanically and electrically connected to each other, even via corners.

DE Die Y-Connectors des FINA support Systems ermöglichen eine ideale Ausleuchtung der gesamten Vitrine, indem unterschiedliche Insets auch über Ecken miteinander mechanisch und elektrisch verbunden werden können.