



# SASSO 100 round adjustable

recessed 1 lamp


**EN** Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; light inset rotatable and tiltable; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

**DE** Runder Einbaustrahler; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; Lichteinsatz dreh- und schwenkbar; präzise Abstrahlcharakteristik durch hochwertige Linsenoptik; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K, colour warm dimming 1800 - 3000 K, tunable white 1800 - 4000 K, tunable white 2700 - 6500 K  
 CRI  $\geq$  90, CRI  $\geq$  92 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)  
 UGR  $\leq$  10, UGR  $\leq$  13, UGR  $\leq$  16, UGR  $\leq$  19  
 up to 127 lm/W  
 L80 / 50000 h, L85 / 50000 h, L90 / 50000 h  
 DALI-2, non DIM  
 front IP40, back IP20

## Types



## Colour



## Mounting set



## Light distributions



360° rotatable,  
30° tiltable



glare control  
(UGR  $\leq$  16)



quick mounting  
in soft acoustic  
ceilings



Colour Warm  
Dimming 1800 –  
3000 K



CRI  $\geq$  95 2  
SDCM  
(optional)



### SASSO 100 round adjustable (tunable white)



#### MEDIUM 33°, DALI-2


| SYSTEM | COLOUR TEMP.                         | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|--------------------------------------|-----------|----------|---|
| 24.1 W | 2700 - 6500 K (tunable w., CRI ≥ 92) | 1800 lm   | 75 lm/W  | 0 4 8 - 2 7 2 0 D 3 <input checked="" type="checkbox"/> M |
| 27.6 W | 1800 - 4000 K (tunable w., CRI ≥ 90) | 1980 lm   | 72 lm/W  | 0 4 8 - 2 7 2 0 L 3 <input checked="" type="checkbox"/> M |

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour traffic white, matt silver. DALI-2 power supply included

#### WIDE FLOOD 53°, DALI-2

| SYSTEM | COLOUR TEMP.                         | LUM. FLUX | EFFICACY | ORDER CODE  |
|--------|--------------------------------------|-----------|----------|---|
| 24.1 W | 2700 - 6500 K (tunable w., CRI ≥ 92) | 1860 lm   | 77 lm/W  | 0 4 8 - 2 7 2 0 D 3 <input checked="" type="checkbox"/> W |
| 27.6 W | 1800 - 4000 K (tunable w., CRI ≥ 90) | 2050 lm   | 74 lm/W  | 0 4 8 - 2 7 2 0 L 3 <input checked="" type="checkbox"/> W |

DALI-2 power supply included



### SASSO 100 round adjustable



#### SPOT 20°, CRI ≥ 90


| FIXTURE               | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|-----------------------|--------------|-----------|----------|---|
| 15.2 W, 36 Vf, 450 mA | 2700 K       | 1740 lm   | 115 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> S |
|                       | 3000 K       | 1800 lm   | 118 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> S |
|                       | 3500 K       | 1840 lm   | 121 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> S |
|                       | 4000 K       | 1880 lm   | 123 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> S |
| 22.7 W, 36 Vf, 650 mA | 2700 K       | 2400 lm   | 106 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> S |
|                       | 3000 K       | 2430 lm   | 107 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> S |
|                       | 3500 K       | 2490 lm   | 110 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> S |
|                       | 4000 K       | 2550 lm   | 112 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> S |

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white.

#### MEDIUM 31°-34°, CRI ≥ 90

| FIXTURE               | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|-----------------------|--------------|-----------|----------|---|
| 15.2 W, 36 Vf, 450 mA | 2700 K       | 1750 lm   | 115 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> M |
|                       | 3000 K       | 1800 lm   | 118 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> M |
|                       | 3500 K       | 1840 lm   | 121 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> M |
|                       | 4000 K       | 1890 lm   | 124 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> M |
| 22.7 W, 36 Vf, 650 mA | 2700 K       | 2410 lm   | 106 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> M |
|                       | 3000 K       | 2440 lm   | 108 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> M |
|                       | 3500 K       | 2500 lm   | 110 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> M |
|                       | 4000 K       | 2560 lm   | 113 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> M |
| 23.8 W, 700 mA        | CWD          | 2060 lm   | 87 lm/W  | 0 4 8 - 2 7 2 0 E 1 <input checked="" type="checkbox"/> M |

The data values for the luminaire luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour traffic white, matt silver. CWD only for DALI-2; not for DIN-RAIL LED Driver



#### Order options

| COLOUR                 | <input checked="" type="checkbox"/> | COLOUR          |          |
|------------------------|-------------------------------------|-----------------|----------|
| jet black RAL 9005     | 1                                   | white aluminium | RAL 9006 |
| matt silver            | 4                                   | traffic black   | RAL 9017 |
| traffic white RAL 9016 | 7                                   |                 |          |
| gold dust RAL 260-M    | 9                                   |                 |          |

**FLOOD 39°, CRI ≥ 90**


| FIXTURE               | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|-----------------------|--------------|-----------|----------|---|
| 15.2 W, 36 Vf, 450 mA | 2700 K       | 1660 lm   | 109 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> F |
|                       | 3000 K       | 1710 lm   | 113 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> F |
|                       | 3500 K       | 1750 lm   | 115 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> F |
|                       | 4000 K       | 1790 lm   | 118 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> F |
| 22.7 W, 36 Vf, 650 mA | 2700 K       | 2290 lm   | 101 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> F |
|                       | 3000 K       | 2320 lm   | 102 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> F |
|                       | 3500 K       | 2380 lm   | 105 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> F |
|                       | 4000 K       | 2430 lm   | 107 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> F |

The data values for the luminaire luminous flux may differ for specific order options by -9%. Luminous flux value refers to colour traffic white.

**WIDE FLOOD 51°-56°, CRI ≥ 90**


| FIXTURE               | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|-----------------------|--------------|-----------|----------|---|
| 15.2 W, 36 Vf, 450 mA | 2700 K       | 1800 lm   | 118 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> W |
|                       | 3000 K       | 1850 lm   | 121 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> W |
|                       | 3500 K       | 1890 lm   | 124 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> W |
|                       | 4000 K       | 1940 lm   | 127 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> W |
| 22.7 W, 36 Vf, 650 mA | 2700 K       | 2470 lm   | 109 lm/W | 0 4 8 - 2 7 2 0 9 1 <input checked="" type="checkbox"/> W |
|                       | 3000 K       | 2500 lm   | 110 lm/W | 0 4 8 - 2 7 2 0 0 1 <input checked="" type="checkbox"/> W |
|                       | 3500 K       | 2560 lm   | 113 lm/W | 0 4 8 - 2 7 2 0 2 1 <input checked="" type="checkbox"/> W |
|                       | 4000 K       | 2620 lm   | 116 lm/W | 0 4 8 - 2 7 2 0 1 1 <input checked="" type="checkbox"/> W |
| 23.8 W, 700 mA        | CWD          | 2290 lm   | 96 lm/W  | 0 4 8 - 2 7 2 0 E 1 <input checked="" type="checkbox"/> W |

CWD only for DALI-2; not for DIN-RAIL LED Driver


**Electrical mounting accessories (optional)****THROUGH WIRING CONNECTION BOX**

| TYPE                      | L-W-H (mm) | ORDER CODE            |
|---------------------------|------------|-----------------------|
| non DIM cable ø 4 – 12 mm | 105-58-30  | 0 0 5 - 2 5 3 1 1 1 0 |
| DALI cable ø 4 – 12 mm    | 105-58-30  | 0 0 5 - 2 5 5 1 1 1 0 |


Linect®-Ready

**Mounting accessories (required)****MOUNTING SET trimless for plasterboard ceilings**

| COLOUR        | PLASTERBOARD CEILING THICKNESS | Ø-H (mm) | ORDER CODE            |
|---------------|--------------------------------|----------|-----------------------|
| traffic white | 12.5/15/25 mm                  | 105-29   | 0 4 8 - 2 7 9 6 1 1 7 |

**MOUNTING SET trimless for soft acoustic ceilings**


| COLOUR        | CEILING THICKNESS | Ø-H (mm) | ORDER CODE            |
|---------------|-------------------|----------|-----------------------|
| traffic white | 25-40 mm          | 114-27   | 0 4 8 - 2 7 9 6 1 9 7 |

**MOUNTING SET with trim for soft acoustic ceilings**


| COLOUR        | CEILING THICKNESS | Ø-H (mm) | ORDER CODE            |
|---------------|-------------------|----------|-----------------------|
| traffic white | 25-40 mm          | 114-25   | 0 4 8 - 2 7 9 6 3 9 7 |

**Order options**


| COLOUR                 | <input checked="" type="checkbox"/> | COLOUR          |          |
|------------------------|-------------------------------------|-----------------|----------|
| jet black RAL 9005     | 1                                   | white aluminium | RAL 9006 |
| matt silver            | 4                                   | traffic black   | RAL 9017 |
| traffic white RAL 9016 | 7                                   |                 |          |
| gold dust RAL 260-M    | 9                                   |                 |          |

**MOUNTING SET with trim for soft acoustic ceilings**


| COLOUR    | CEILING THICKNESS | Ø-H (mm) | ORDER CODE            |
|-----------|-------------------|----------|-----------------------|
| jet black | 25-40 mm          | 114-25   | 0 4 8 - 2 7 9 6 3 9 8 |

**MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm**

| COLOUR          | Ø-H (mm) | ORDER CODE            |
|-----------------|----------|-----------------------|
| traffic white   | 118-40   | 0 4 8 - 2 7 9 6 3 1 7 |
| jet black       | 118-40   | 0 4 8 - 2 7 9 6 3 1 8 |
| white aluminium | 118-40   | 0 4 8 - 2 7 9 6 3 1 G |


**Mounting accessories (optional)****EXPOSED CONCRETE MOUNTING HOUSING**

| COLOUR          | L-W-H (mm)  | ORDER CODE            |
|-----------------|-------------|-----------------------|
| white aluminium | 230-230-162 | 0 4 8 - 2 7 9 5 2 1 0 |

**PRIMED CONCRETE MOUNTING HOUSING**

| L-W-H (mm)  | ORDER CODE            |
|-------------|-----------------------|
| 614-307-120 | 0 4 8 - 2 6 9 5 1 1 0 |


order mounting set separately

**Mounting tools accessories (optional)****MOUNTING TOOL for soft acoustic ceilings**

| COLOUR        | L-W-H (mm) | ORDER CODE            |
|---------------|------------|-----------------------|
| traffic black | 104-104-35 | 0 4 8 - 2 7 9 5 9 1 8 |

**Electrical accessories (required)****POWER SUPPLY PC2**

| TYPE                    | INPUT VOLTAGE | EFFICIENCY | L-W-H (mm) | ORDER CODE        |
|-------------------------|---------------|------------|------------|-------------------|
| 450 mA   21 W   non DIM | 198-264 V AC  | η 86 %     | 143-43-30  | 0 0 2 - 9 0 7 6 6 |
| 450 mA   28 W   DALI-2  | 176-264 V AC  | η 85 %     | 143-43-30  | 0 0 2 - 9 0 7 6 7 |
| 700 mA   28 W   DALI-2  | 176-264 V AC  | η 85 %     | 143-43-30  | 0 0 2 - 9 0 7 7 6 |
| 650 mA   31 W   non DIM | 198-264 V AC  | η 88 %     | 143-43-30  | 0 0 2 - 9 0 7 8 0 |
| 650 mA   28 W   DALI-2  | 176-264 V AC  | η 85 %     | 143-43-30  | 0 0 2 - 9 0 7 8 9 |

**Electrical accessories (optional)****DIN RAIL POWER SUPPLY BASIC 48 V**

| TYPE        | INPUT VOLTAGE | EFFICIENCY | L-W-H (mm) | ORDER CODE            |
|-------------|---------------|------------|------------|-----------------------|
| 160 W   PC2 | 220-240 V AC  | η 94 %     | 72-90-63   | 0 0 5 - 6 5 2 0 2 1 0 |

Lifetime &gt;100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

**Order options**

| COLOUR                 | <input checked="" type="checkbox"/> | COLOUR          |          |
|------------------------|-------------------------------------|-----------------|----------|
| jet black RAL 9005     | 1                                   | white aluminium | RAL 9006 |
| matt silver            | 4                                   | traffic black   | RAL 9017 |
| traffic white RAL 9016 | 7                                   |                 |          |
| gold dust RAL 260-M    | 9                                   |                 |          |

**DIN RAIL LED DRIVER**

| TYPE   | L-W-H (mm) | ORDER CODE            |
|--|------------|-----------------------|
| DALI-2 DT6 1-2 addresses   | 36-88-59   | 0 0 5 - 6 1 2 1 0 3 0 |
| 200 - 1050mA settable const. current   2×42W   48V DC   U OUT 10-40V |            |                       |

**POWER SUPPLY PRE-WIRED with junction box 28 W, PC2**

| TYPE             | INPUT VOLTAGE | EFFICIENCY | ORDER CODE          |
|------------------|---------------|------------|---------------------|
| 450 mA   DALI-2  | 176-264 V AC  | η 85 %     | 0 0 2 - 9 0 7 6 7 A |
| 650 mA   DALI-2  | 176-264 V AC  | η 85 %     | 0 0 2 - 9 0 7 8 9 A |
| 700 mA   DALI-2  | 176-264 V AC  | η 85 %     | 0 0 2 - 9 0 7 7 6 A |
| 450 mA   non DIM | 198-264 V AC  | η 88 %     | 0 0 2 - 9 0 7 6 6 A |
| 650 mA   non DIM | 198-264 V AC  | η 88 %     | 0 0 2 - 9 0 7 8 0 A |
| 700 mA   non DIM | 198-264 V AC  | η 88 %     | 0 0 2 - 9 0 7 7 4 A |

**Optical accessories (optional)****HONEYCOMB LOUVER for BO 55 | JUST 55 | SASSO 100**

| COLOUR    | Ø-H (mm) | ORDER CODE            |
|-----------|----------|-----------------------|
| jet black | 50-3     | 0 0 7 - 1 9 6 5 5 9 8 |

**Order options**

| COLOUR                 |   | COLOUR          |          |
|------------------------|---|-----------------|----------|
| jet black RAL 9005     | 1 | white aluminium | RAL 9006 |
| matt silver            | 4 | traffic black   | RAL 9017 |
| traffic white RAL 9016 | 7 |                 |          |
| gold dust RAL 260-M    | 9 |                 |          |

# Casagrande Luxury Lifestyle, Lucerne

Switzerland

**Architect**  
Obrist interior AG

**Lighting Design**  
Obrist interior AG

**Photographer**  
Obrist interior AG



## Used products




**TULA suspended**



**JUST 55 MOVE IT  
25 / 25 S / 45**



**MOVE IT 25 trimless  
system**



**MOVE IT 25 S  
trimless system**



**OPAL HIGH  
PERFORMANCE  
MOVE IT 25 S**




**OPAL HIGH  
PERFORMANCE  
MOVE IT 25**




**SPOTLINE MOVE IT  
25**



**SQUADRO  
wallwasher recessed**




**SASSO 100 round  
downlight recessed 1  
lamp**



**SASSO 100 round  
wallwasher/floor  
recessed 1 lamp**



**SASSO 100 round  
adjustable recessed 1  
lamp**



**SASSO 100 round  
wallwasher recessed  
1 lamp**

