




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K, tunable white 2700 - 6500 K
CRI ≥ 90 / 2 SDCM (initial MacAdam), 3 SDCM (initial MacAdam)
up to 107 lm/W
L80 / 50000 h, L80 / 75000 h, L85 / 50000 h
DALI-2, non DIM
front IP20

Types



Colours

Mounting set

Light distributions

SASSO 100 round wallwasher

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

CRI ≥ 95 2 SDCM (optional)



SASSO 100 round wallwasher (tunable white)



WALLWASHER 2700 - 6500 K, CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.1 W	tunable w.	593 lm	59 lm/W	0 4 8 - 2 7 4 0 D 3 ◪ A

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white. DALI-2 power supply included


SASSO 100 round wallwasher

WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
15.8 W,	2700 K	1680 lm	107 lm/W	0 4 8 - 2 7 4 0 9 1 ◪ A
36 Vf,	3000 K	1580 lm	100 lm/W	0 4 8 - 2 7 4 0 0 1 ◪ A
450 mA	3500 K	1650 lm	104 lm/W	0 4 8 - 2 7 4 0 2 1 ◪ A
	4000 K	1580 lm	100 lm/W	0 4 8 - 2 7 4 0 1 1 ◪ A
23.7 W,	2700 K	2320 lm	98 lm/W	0 4 8 - 2 7 4 0 9 1 ◪ A
36 Vf,	3000 K	2180 lm	92 lm/W	0 4 8 - 2 7 4 0 0 1 ◪ A
650 mA	3500 K	2270 lm	96 lm/W	0 4 8 - 2 7 4 0 2 1 ◪ A
	4000 K	2180 lm	92 lm/W	0 4 8 - 2 7 4 0 1 1 ◪ A

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white, matt silver.

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105·58·30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

Mounting accessories (required)




MOUNTING SET trimless for plasterboard ceilings

COLOUR	PLASTERBOARD CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	12.5/15/20/25 mm	105·29	0 4 8 - 2 7 9 6 1 1 7



MOUNTING SET trimless for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	114·27	0 4 8 - 2 7 9 6 1 9 7




MOUNTING SET with trim for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	traffic white	25-40 mm	114·25	0 4 8 - 2 7 9 6 3 9 7

Order options


COLOUR	◪
jet black RAL 9005	1
matt silver	4
traffic white RAL 9016	7
gold dust RAL 260-M	9

COLOUR	
white aluminium	RAL 9006
traffic black	RAL 9017



MOUNTING SET with trim for soft acoustic ceilings

TYPE	COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
For Rockfon Mono® Acoustic	jet black	25-40 mm	114·25	048-2796398



MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm


COLOUR	Ø·H (mm)	ORDER CODE
traffic white	118·40	048-2796317
jet black	118·40	048-2796318
white aluminium	118·40	048-279631G

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230·230·162	048-2795210




PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
614·307·120	048-2695110

order mounting set separately

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings

COLOUR	L·W·H (mm)	ORDER CODE
traffic black	104·104·35	048-2795918


Electrical accessories (required)

POWER SUPPLY PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
450 mA | 21 W | non DIM	198-264 V AC	η 86 %	143·43·30	002-90766
450 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-90767
650 mA | 28 W | non DIM	198-264 V AC	η 88 %	143·43·30	002-90780
650 mA | 28 W | DALI-2	176-264 V AC	η 85 %	143·43·30	002-90789

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-6520210

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

Order options

COLOUR

white aluminium	RAL 9006
traffic black	RAL 9017

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40 V SELV

POWER SUPPLY PRE-WIRED with junction box 28 W, PC2

TYPE	INPUT VOLTAGE	EFFICIENCY	ORDER CODE
450 mA | DALI-2	176-264 V AC	η 85 %	002-90767A
650 mA | DALI-2	176-264 V AC	η 85 %	002-90789A
700 mA | DALI-2	176-264 V AC	η 85 %	002-90776A
450 mA | non DIM	198-264 V AC	η 88 %	002-90766A
650 mA | non DIM	198-264 V AC	η 88 %	002-90780A
700 mA | non DIM	198-264 V AC	η 88 %	002-90774A

2 power supplies for 2 lamps variants necessary

Pretzhof

Italy

Architect
KUPArchitekten


Photographer
Oskar Da Riz



Used products




SASSO 100 round adjustable recessed 1 lamp



SASSO 100 round downlight recessed 1 lamp



SASSO 100 round wallwasher/floor recessed 1 lamp



SASSO 100 round wallwasher recessed 1 lamp

No liability is assumed for typographical or printing errors.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com




PRETZHOF
SHOP & BISTRO
PRETZHOF
PRETZHOF
SHOP
BISTRO






BEER
MEKATZER GOLD
MEKATZER WEIZEN





