



Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90 / 3 SDCM (initial MacAdam)
up to ↓ 9,360 lm / ↑ 9,340 lm
up to 126 lm/W
L90 / 50000 h
Cover: Opal
DALI-2
IP20

Types





Colours



Light distributions



INO TRIPLE circle

suspended

EN 3 pcs. ring-shaped light fittings in rolled and seamlessly welded extruded aluminium profile; surface powder coated; pendant fitting with cable suspension; height adjustment without tools; light fitting individually height adjustable; incl. transparent feed; 3 pcs. electronic operating units installed in the canopy; completely homogeneously illuminated, satinised PMMA cover; inwards facing emission characteristics; direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; canopy with 2 cable openings and plug-in terminal for through wiring


DE 3 Stk. ringförmige Leuchtenkörper aus gerolltem und nahtlos verschweißtem Aluminiumstrangpressprofil; Oberfläche pulverbeschichtet; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung; Leuchtenkörper individuell höhenverstellbar; inkl. transparenter Einspeiseleitung; 3 Stk. elektronische Betriebsgeräte im Baldachin verbaut; absolut homogen ausgeleuchtete, satinierte PMMA-Abdeckung; nach innen gerichtete Abstrahlcharakteristik; direkt/indirekte Abstrahlcharakteristik für zusätzliche Akzentuierung der Decke und mehr Sehkomfort; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin mit 2 Kabelöffnungen und Steckklemme für Weiterverdrahtung




DiiA® standards 251, 252, 253



direct / indirect illumination




tunable white 2700 – 6500 K (optional)



CRI ≥ 98 XPECTRUM (optional)





INO TRIPLE circle suspended

CRI ≥ 90 · 220-240 V · DALI 3 ADDR. · X-PERT · X-PERT

OPAL CRI ≥ 90, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
149.0 W	2700 K	↧8110/↥8090 lm	109 lm/W	0 3 4 - 3 8 4 5 4 3 ◪ H
	3000 K	↧8510/↥8490 lm	114 lm/W	0 3 4 - 3 8 4 5 5 3 ◪ H
	4000 K	↧9360/↥9340 lm	126 lm/W	0 3 4 - 3 8 4 5 6 3 ◪ H

Order options

COLOUR	◪
pure white RAL 9010	7
jet black RAL 9005	8
white aluminium RAL 9006	G
special colours	X