

MITA circle 200

recessed


EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

DE Ringförmiger Leuchtenkörper aus Aluminiumdruckguss; extrem schlanke Bauform; Einbauleuchte mit umlaufendem Rand; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; hochglänzender Reflektor mit Facettenoptik; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K, tunable white
 2700 - 6500 K
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM
 (initial MacAdam)
 UGR ≤ 19
 up to 139 lm/W
 L90 / 50000 h
 DALI-2
 Opal, Reflector
 IP20

Types



Colour



Reflector




Light distributions




suitable for
 plasterboard or
 grid ceilings



DIN EN 12464-1
 UGR ≤ 19



tunable white
 2700 – 6500 K




MITA CIRCLE 200 opal trim



OPAL DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
17.2 W	3000 K, CRI ≥ 90	1550 lm	90 lm/W	0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> O
	4000 K, CRI ≥ 90	1670 lm	97 lm/W	0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> O
17.5 W	3000 K, CRI ≥ 80	1760 lm	101 lm/W	0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> O
	4000 K, CRI ≥ 80	1830 lm	105 lm/W	0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> O
21.6 W	tunable w., CRI ≥ 90	1820 lm	84 lm/W	0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> O




MITA CIRCLE 200 reflector trim



REFLECTOR DALI-2

SYSTEM	COLOUR TEMP.	REFLECTOR	LUM. FLUX	EFFICACY	ORDER CODE
13.2 W	3000 K, CRI ≥ 90	chrome	1580 lm	120 lm/W	0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> R
		dark chr.	1130 lm	86 lm/W	0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> B
	4000 K, CRI ≥ 90	chrome	1700 lm	129 lm/W	0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> R
		dark chr.	1220 lm	92 lm/W	0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> B
13.5 W	3000 K, CRI ≥ 80	chrome	1800 lm	133 lm/W	0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> R
		dark chr.	1290 lm	96 lm/W	0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> B
	4000 K, CRI ≥ 80	chrome	1870 lm	139 lm/W	0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> R
		dark chr.	1340 lm	99 lm/W	0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> B
15.6 W	tunable w., CRI ≥ 90	chrome	1750 lm	112 lm/W	0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> R
		dark chr.	1250 lm	80 lm/W	0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> B



Order options

COLOUR	
traffic white RAL 9016	<input checked="" type="checkbox"/> 7
jet black RAL 9005	<input checked="" type="checkbox"/> 8