



## SASSO 60 square wallwasher/floor

recessed 1 lamp


**EN** Square recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

**DE** Quadratischer Einbaustrahler; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI ≥ 90 / 2 SDCM (initial MacAdam)  
 up to 120 lm/W  
 L85 / 50000 h  
 DALI-2, non DIM  
 front IP20

### Types



### Colour



### Mounting set



### Light distributions



wallwasher/  
wallwasher floor  
inset



60 mm  
recessed depth



CRI ≥ 95 2  
SDCM  
(optional)




## SASSO 60 square wallwasher/floor




### WALLWASHER FLOOR CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W,	2700 K	1060 lm	120 lm/W	0 4 8 - 2 6 5 1 9 1 <input checked="" type="checkbox"/> W
36 Vf,	3000 K	997 lm	113 lm/W	0 4 8 - 2 6 5 1 0 1 <input checked="" type="checkbox"/> W
250 mA	3500 K	1040 lm	117 lm/W	0 4 8 - 2 6 5 1 2 1 <input checked="" type="checkbox"/> W
	4000 K	997 lm	113 lm/W	0 4 8 - 2 6 5 1 1 1 <input checked="" type="checkbox"/> W



## Electrical mounting accessories (optional)




### THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable $\varnothing$ 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable $\varnothing$ 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

## Mounting accessories (required)



### MOUNTING SET trimless for plasterboard ceilings


COLOUR	PLASTERBOARD CEILING THICKNESS	L-W-H (mm)	ORDER CODE
traffic white	12.5/15/25 mm	72-72-29	0 4 8 - 2 6 9 7 1 1 7



### MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
traffic white	80-80-21	0 4 8 - 2 6 9 7 3 1 7
jet black	80-80-21	0 4 8 - 2 6 9 7 3 1 8
white aluminium	80-80-21	0 4 8 - 2 6 9 7 3 1 G

## Mounting accessories (optional)



### PRIMED CONCRETE MOUNTING HOUSING

L-W-H (mm)	ORDER CODE
614-307-120	0 4 8 - 2 6 9 5 1 1 0

order mounting set separately

## Order options


COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
matt silver	4		
traffic white RAL 9016	7		
gold dust RAL 260-M	9		

### Electrical accessories (required)

#### POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
10 W   non DIM	$\eta$ 80 %	65-39-20	0 0 2 - 9 0 7 4 2
15 W   DALI-2	$\eta$ 87 %	165-29-21	0 0 2 - 9 0 7 4 8

### Electrical accessories (optional)



#### DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W   PC2	220-240 V AC	$\eta$ 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

#### DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10–40V

#### POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA   15 W   DALI-2	$\eta$ 87 %	0 0 2 - 9 0 7 9 0 A
250 mA   15 W   DALI-2	$\eta$ 87 %	0 0 2 - 9 0 7 4 8 A
300 mA   15 W   non DIM	$\eta$ 84 %	0 0 2 - 9 0 7 7 1 A
250 mA   10 W   non DIM	$\eta$ 80 %	0 0 2 - 9 0 7 4 2 A

#### POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
300 mA	$\eta$ 87 %	185-30-21	0 0 2 - 9 0 7 7 0
250 mA	$\eta$ 87 %	185-30-21	0 0 2 - 9 0 7 4 7

### Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	
jet black RAL 9005	1	white aluminium	RAL 9006
matt silver	4		
traffic white RAL 9016	7		
gold dust RAL 260-M	9		