



# SASSO 60 square wallwasher

recessed 2 lamps

**EN** Square recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

**DE** Quadratischer Einbaustrahler; werkzeuglose Montage im Montageset durch Kugelschnappsystem; Oberfläche lackiert; mit umlaufendem Rand; zweiflämmig; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI ≥ 90 / 2 SDCM (initial MacAdam)  
 up to 117 lm/W  
 L85 / 50000 h  
 DALI-2, non DIM  
 front IP20

## Types

double trim



## Colour



## Mounting set



## Light distributions




wallwasher/  
wallwasher floor  
inset



60 mm  
recessed depth



CRI ≥ 95 2  
SDCM  
(optional)




## SASSO 60 square wallwasher




### WALLWASHER CRI ≥ 90

| FIXTURE  | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE  |
|----------|--------------|-----------|----------|---|
| 2x8.9 W, | 2700 K       | 2x1030 lm | 117 lm/W | 0 4 8 - 2 6 5 1 9 1 <input checked="" type="checkbox"/> A |
| 36 Vf,   | 3000 K       | 2x972 lm  | 110 lm/W | 0 4 8 - 2 6 5 1 0 1 <input checked="" type="checkbox"/> A |
| 250 mA   | 3500 K       | 2x1010 lm | 114 lm/W | 0 4 8 - 2 6 5 1 2 1 <input checked="" type="checkbox"/> A |
|          | 4000 K       | 2x972 lm  | 110 lm/W | 0 4 8 - 2 6 5 1 1 1 <input checked="" type="checkbox"/> A |

The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.



## Electrical mounting accessories (optional)




### THROUGH WIRING CONNECTION BOX

| TYPE                      | L-W-H (mm) | ORDER CODE            |
|---------------------------|------------|-----------------------|
| non DIM cable ø 4 – 12 mm | 105-58-30  | 0 0 5 - 2 5 3 1 1 1 0 |
| DALI cable ø 4 – 12 mm    | 105-58-30  | 0 0 5 - 2 5 5 1 1 1 0 |

Linect®-Ready

## Mounting accessories (required)



### MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm


| L-W-H (mm) | ORDER CODE  |
|------------|---|
| 147-81-35  | 0 4 8 - 2 6 9 9 3 1 <input checked="" type="checkbox"/> |

## Electrical accessories (required)

### POWER SUPPLY 250 mA, 198-264 V AC, PC2

| TYPE           | EFFICIENCY | L-W-H (mm) | ORDER CODE        |
|----------------|------------|------------|-------------------|
| 10 W   non DIM | η 80 %     | 65-39-20   | 0 0 2 - 9 0 7 4 2 |
| 15 W   DALI-2  | η 87 %     | 165-29-21  | 0 0 2 - 9 0 7 4 8 |

## Electrical accessories (optional)



### DIN RAIL POWER SUPPLY BASIC 48 V

| TYPE        | INPUT VOLTAGE | EFFICIENCY | L-W-H (mm) | ORDER CODE            |
|-------------|---------------|------------|------------|-----------------------|
| 160 W   PC2 | 220-240 V AC  | η 94 %     | 72-90-63   | 0 0 5 - 6 5 2 0 2 1 0 |

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

### DIN RAIL LED DRIVER

| TYPE                                    | L-W-H (mm) | ORDER CODE            |
|---|------------|-----------------------|
| DALI-2 DT6 1-2 addresses / DT8 1 adress | 36-88-59   | 0 0 5 - 6 1 2 1 0 3 0 |

200 -1050 mA settable const. current | 2x42W | 48V DC | U OUT 10-40V SELV

## Order options

| COLOUR                 |                                       | COLOUR                   |                                       |
|------------------------|---------------------------------------|--------------------------|---------------------------------------|
| jet black RAL 9005     | 1 <input checked="" type="checkbox"/> | traffic white RAL 9016   | 7 <input checked="" type="checkbox"/> |
| matt silver            | 4                                     | jet black RAL 9005       | 8                                     |
| traffic white RAL 9016 | 7                                     | white aluminium RAL 9006 | G                                     |
| gold dust RAL 260-M    | 9                                     |                          |                                       |

**POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2**

| TYPE                    | EFFICIENCY  | ORDER CODE          |
|-------------------------|-------------|---------------------|
| 300 mA   15 W   DALI-2  | $\eta$ 87 % | 0 0 2 - 9 0 7 9 0 A |
| 250 mA   15 W   DALI-2  | $\eta$ 87 % | 0 0 2 - 9 0 7 4 8 A |
| 300 mA   15 W   non DIM | $\eta$ 84 % | 0 0 2 - 9 0 7 7 1 A |
| 250 mA   10 W   non DIM | $\eta$ 80 % | 0 0 2 - 9 0 7 4 2 A |

**POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2**

| TYPE   | EFFICIENCY  | L-W-H (mm) | ORDER CODE        |
|--------|-------------|------------|-------------------|
| 300 mA | $\eta$ 87 % | 185-30-21  | 0 0 2 - 9 0 7 7 0 |
| 250 mA | $\eta$ 87 % | 185-30-21  | 0 0 2 - 9 0 7 4 7 |

**Order options**

| COLOUR                 | <input checked="" type="checkbox"/> | COLOUR                   | <input checked="" type="checkbox"/> |
|------------------------|-------------------------------------|--------------------------|-------------------------------------|
| jet black RAL 9005     | 1                                   | traffic white RAL 9016   | 7                                   |
| matt silver            | 4                                   | jet black RAL 9005       | 8                                   |
| traffic white RAL 9016 | 7                                   | white aluminium RAL 9006 | G                                   |
| gold dust RAL 260-M    | 9                                   |                          |                                     |