

Quickinfo

3000 K, 4000 K
CRI ≥ 80, CRI ≥ 90 / 3 SDCM (initial MacAdam)
UGR ≤ 16, UGR ≤ 19
up to 176 lm/W
L90 / 100000 h
DALI-2, DALI-2 ESSENTIAL sensor
IP20

Types



Colours

Inset

Light distributions

ENVIVA

recessed

EN Luminaire housing from extruded aluminium profile, angular design; recessed luminaire with trim; suitable for installation in 12.5 mm ceilings; easy mounting without need to cut the substructure; surface raw or powder coated; linear light inset made of plastic; fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; or high quality reflector with micro-faceted, aluminium-vaporised surface; precise radiation characteristic with symmetrical light distribution; efficient LEDs with very good colour rendering; optionally with sensor; incl. external converter for ceiling insertion

DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; Einbauleuchte mit umlaufendem Rand; geeignet für den Einbau in 12,5 mm Decken; einfache Montage ohne Schneiden der Unterkonstruktion; Oberfläche roh oder pulverbeschichtet; linearer Lichteinsatz aus Kunststoff; bestückt mit LED Einzellichtpunkten; gute Entblendung durch zurückversetzte Lichtpunktebene; trotzdem erhöhte Effizienz durch spezielle Linsentechnik; eingesetzte Linsen mit wide flood Abstrahlcharakteristik; oder hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit symmetrischer Lichtverteilung; effiziente LEDs mit sehr guter Farbwiedergabe; wahlweise mit Sensor; inkl. externem Konverter für Deckeneinwurf



DIN EN 12464-1
UGR ≤ 16



up to 176 lm/W
(high efficiency)



ESSENTIAL
sensor available

ENVIVA louver trim

CRI ≥90 · UGR ≤19 · cd/m² ≤1500 · 220-240 V · 1 ADDR. · X-PERT · X-PERT · presence · brightness

LOUVER

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1221 mm	3000 K	80	3260 lm	165 lm/W	067-00345 ◆ ◪ ■ X
			90	2840 lm	144 lm/W	067-00340 ◆ ◪ ■ X
		4000 K	80	3470 lm	176 lm/W	067-00346 ◆ ◪ ■ X
			90	2840 lm	144 lm/W	067-00341 ◆ ◪ ■ X
25.1 W	1521 mm	3000 K	80	4120 lm	164 lm/W	067-00355 ◆ ◪ ■ X
			90	3590 lm	143 lm/W	067-00350 ◆ ◪ ■ X
		4000 K	80	4380 lm	175 lm/W	067-00356 ◆ ◪ ■ X
			90	3590 lm	143 lm/W	067-00351 ◆ ◪ ■ X

sensor version +41mm



ENVIVA spotline trim

CRI ≥90 · UGR ≤16 · cd/m² ≤1500 · 220-240 V · 1 ADDR. · X-PERT · X-PERT · presence · brightness

SPOTLINE

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.7 W	1221 mm	3000 K	80	3180 lm	161 lm/W	067-10345 ◆ ◪ ■$_1$ W
			90	2770 lm	141 lm/W	067-10340 ◆ ◪ ■$_1$ W
		4000 K	80	3390 lm	172 lm/W	067-10346 ◆ ◪ ■$_1$ W
			90	2770 lm	141 lm/W	067-10341 ◆ ◪ ■$_1$ W
25.1 W	1521 mm	3000 K	80	4020 lm	160 lm/W	067-10355 ◆ ◪ ■$_1$ W
			90	3500 lm	139 lm/W	067-10350 ◆ ◪ ■$_1$ W
		4000 K	80	4280 lm	171 lm/W	067-10356 ◆ ◪ ■$_1$ W
			90	3500 lm	139 lm/W	067-10351 ◆ ◪ ■$_1$ W

sensor version +41mm

ENVIVA lens trim

CRI ≥90 · UGR ≤19 · cd/m² ≤3000 · 220-240 V · 1 ADDR. · X-PERT · X-PERT · presence · brightness

LENS

SYSTEM	LENGTH	COLOUR TEMP.	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
19.6 W	1221 mm	3000 K	80	3240 lm	165 lm/W	067-20345 ◆ ◪ W
			90	2820 lm	144 lm/W	067-20340 ◆ ◪ W
		4000 K	80	3450 lm	176 lm/W	067-20346 ◆ ◪ W
			90	2820 lm	144 lm/W	067-20341 ◆ ◪ W
24.8 W	1521 mm	3000 K	80	4100 lm	165 lm/W	067-20355 ◆ ◪ W
			90	3570 lm	144 lm/W	067-20350 ◆ ◪ W
		4000 K	80	4370 lm	176 lm/W	067-20356 ◆ ◪ W
			90	3570 lm	144 lm/W	067-20351 ◆ ◪ W

sensor version +41mm



Order options

CONTROL ◆		COLOUR ◪		INSET ■		INSET ■$_1$	
DALI-2	3	aluminium raw	0	chrome reflector	4	traffic white RAL 9016	7
DALI-2 ESSENTIAL sensor	B	traffic white RAL 9016	7	black reflector	8	jet black RAL 9005	8
		jet black RAL 9005	8				