



MINO 25

suspended


EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 25 x 25 mm); no visible screws; surface raw or powder coated; pendant fitting with height-adjustable cable suspension; incl. flat cable for power supply; high quality reflector with micro-faceted, aluminum-vaporised surface; or fitted with single LED light points; good glare reduction due to recessed light point plane; despite this increased efficiency through special lens technology; inserted lenses with wide flood radiation characteristic; precise radiation characteristic with symmetrical light distribution; or completely homogeneously illuminated, opal cover; converter integrated into luminaire housing; energy-efficient LEDs with very good colour rendering; canopy for through wiring

DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; extrem schlanke Bauform (nur 25 x 25 mm); keine sichtbaren Schrauben; Oberfläche roh oder pulverbeschichtet; abgependelt mit höhenverstellbarer Seilabhängung; inkl. Flachkabel zur Einspeisung; hochwertiger Reflektor mit mikro-facettierter, aluminiumbedampfter Oberfläche; oder bestückt mit LED Einzellichtpunkten; gute Entblendung durch zurückversetzte Lichtpunktebene; trotzdem erhöhte Effizienz durch spezielle Linsentechnik; eingesetzte Linsen mit wide flood Abstrahlcharakteristik; präzise Abstrahlcharakteristik mit symmetrischer Lichtverteilung; oder absolut homogen ausgeleuchtete, opale Abdeckung; Konverter im Leuchtenkörper integriert; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin für Weiterverdrahtung

Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90 / 3 SDCM
 (initial MacAdam)
 UGR ≤ 16, UGR ≤ 19
 up to 168 lm/W
 L90 / 100000 h
 Cover: Opal, Wideflood
 DALI-2
 IP20

Types



Colours



Inset




Light distributions




black & chrome
louver



up to 168 lm/W
(high efficiency)



super slim
design





MINO 25 opal suspended




OPAL DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
9.5 W	1004 mm	80	1220 lm	128 lm/W	0 4 3 - 0 2 2 1 : 3 ■ O
		90	1000 lm	105 lm/W	0 4 3 - 0 2 2 1 : 3 ■ O
18.3 W	2004 mm	80	2450 lm	134 lm/W	0 4 3 - 0 2 2 2 : 3 ■ O
		90	2000 lm	109 lm/W	0 4 3 - 0 2 2 2 : 3 ■ O
25.2 W	2754 mm	80	3370 lm	134 lm/W	0 4 3 - 0 2 2 3 : 3 ■ O
		90	2760 lm	110 lm/W	0 4 3 - 0 2 2 3 : 3 ■ O

The data values for the luminous flux may differ for specific order options by -12%. Luminous flux value refers to colour temperature 4000 K.





MINO 25 louver suspended




LOUVER DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1730 lm	162 lm/W	0 4 3 - 0 2 0 1 : 3 ■ ■ X
		90	1420 lm	133 lm/W	0 4 3 - 0 2 0 1 : 3 ■ ■ X
20.6 W	2004 mm	80	3470 lm	168 lm/W	0 4 3 - 0 2 0 2 : 3 ■ ■ X
		90	2840 lm	138 lm/W	0 4 3 - 0 2 0 2 : 3 ■ ■ X
27.5 W	2754 mm	80	4630 lm	168 lm/W	0 4 3 - 0 2 0 3 : 3 ■ ■ X
		90	3790 lm	138 lm/W	0 4 3 - 0 2 0 3 : 3 ■ ■ X

The data values for the luminous flux may differ for specific order options by -6%. Luminous flux value refers to colour temperature 4000 K.




MINO 25 spotline suspended



SPOTLINE DALI-2

SYSTEM	LENGTH	CRI ≥	LUM. FLUX	EFFICACY	ORDER CODE
10.7 W	1004 mm	80	1710 lm	160 lm/W	0 4 3 - 0 2 1 1 : 3 ■ ■ W
		90	1400 lm	131 lm/W	0 4 3 - 0 2 1 1 : 3 ■ ■ W
20.6 W	2004 mm	80	3410 lm	166 lm/W	0 4 3 - 0 2 1 2 : 3 ■ ■ W
		90	2790 lm	135 lm/W	0 4 3 - 0 2 1 2 : 3 ■ ■ W
27.5 W	2754 mm	80	4560 lm	166 lm/W	0 4 3 - 0 2 1 3 : 3 ■ ■ W
		90	3730 lm	136 lm/W	0 4 3 - 0 2 1 3 : 3 ■ ■ W

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inset traffic white colour temperature 4000 K.



Order options

COLOUR TEMPERATURE	COLOUR TEMPERATURE	COLOURS	INSET
3000 K	3000 K	aluminium raw / Cable white	chrome reflector
4000 K	4000 K	aluminium raw / Cable black	black reflector
		signal white / Cable white	
		signal black / Cable black	

INSET	COLOUR
traffic white RAL 9016	signal white RAL 9003
jet black RAL 9005	signal black RAL 9004